



GAS CONNECTOR COMPLETE KIT



Welded Construction

360° Heavy Duty welds on both ends increases durability compared to industry standard crimped ends.

Corrugated Tubing

Stainless steel corrugated tubing built to be flexible for ease of installation.

Radial Wrap


Heavy Duty stainless steel radial wrap prevents hose from stretching.

PVC Protective Coating

PVC protective coating with antimicrobial agent for easy cleaning.

Rotational Ends

360° rotational ends provide versatility and ease during installation.



True Length

As opposed to industry standard of shortening advertised length by 3-1/2"



One-Handed Quick Disconnect

360° stainless steel ball bearings securely lock Quick Disconnect in place.



Gas Valve

Ball valve is required by code to allow for manual shutoff within 5 ft. of appliance.



90° Elbows

Elbows allow for versatility in tight conditions during installation.



Restraining Kit

Comes pre-cut 12" shorter than overall length of hose to prevent hose from being pulled too far. Easily disconnects for cleaning and maintenance.

Includes mounting hardware.

Available in any combination of interior size & lengths seen here:

Interior Sizes:

1/2"

3/4"

1"

1-1/4"

Lengths:

24"

36"

48"

60"


72"

OPTIONAL COMPONENTS



Caster Positioning Chocks

Creates a home position for movable kitchen equipment. Stainless steel construction eliminates cracking commonly seen with plastic caster positioning sets. Mounting hardware included for easy installation. (2) chocks per set.



SwivelKing™

Durable stainless steel construction with dual 360° rotation significantly reduces stress and extends life of hose.