



# ARTISAN 3 DECK OVEN



**Artisan Stone Deck Oven, Individual Programmable Control per Chamber, Individual Shot Steam per Chamber, Standard One Piece Shipment, Single Electrical Connection, Single Water & Drain Connection, Stainless Steel Construction, Multiple Deck Heights (6", 8", 10", 12"), 1" Thick Refractory Stone Deck, 99 Hour Delay-Start Timer, Standard Heavy Duty Legs with Casters, Economy Mode for Energy Saving**



PROJECT \_\_\_\_\_

ITEM NO. \_\_\_\_\_

NOTES \_\_\_\_\_

MODEL NUMBER: **3 T**

**FEATURES**

- Independent Baking Decks (up to 4) with Digital Control Panels
- Deck Capacity of 1, 2, 3 or 4 Pans
- Deck Heights
  - 6" (152mm)
  - 8" (204mm) STANDARD
  - 10" (254mm)
  - 12" (305mm)
- 600°F (316°C) Max Bake Temperature
- Independent Temperature Control for Upper & Lower Deck Elements, Plus Front Temperature Loss Control
- Independent Shot Steam Per Deck with Steam Box On/Off Control
- 99 Hour Delay Start Up Timer & Economy Mode

**CONSTRUCTION**

- Stainless Steel Construction
- 1" (25 mm) Refractory Stone Deck
- Single Point Connection for Electrical, Drain & Water
- Fully Insulated Illuminated
- Fully Retracting Doors (Save Space when Loading & Unloading)
- Legs with Swivel Casters (2 locking)
- One Piece Shipment

**OPTIONS & ACCESSORIES**

- Marine Specification
- Water Filter (50-1530)
- Standard Proofer for 1 - 2 Decks (ES3T)
- Low Profile Proofer for 3 Decks (ES3TP)
- Stainless Steel Deck
- Non-Functional Eyebrow Canopy (EH3T)
- Loaf Loader (LL)
- Single Phase Electrical
- 380-415V Electrical Configuration

**CLEARANCES**

- 1" (25mm) Sides & Back
- 6" (153 mm) Top

**WARRANTY**

- One Year Labor & Two Year Parts

**PLEASE NOTE**


- One Single Electrical Drain, Water Connection. Multiple Decks are inter-connected.
- Electrical Inlet located at the back on top right hand corner.
- For Steam Efficiency, use minimum water inlet pressure 50 PSI.
- To prevent steam system scale issues, install water softener rated for a



\*SHOWN IN 3T2



3T - End Loaded





PROJECT \_\_\_\_\_

ITEM NO. \_\_\_\_\_

NOTES \_\_\_\_\_

MODEL NUMBER: **3 T**


### DECK HEIGHT CONFIGURATOR

#### 1. Optional Eyebrow Canopy



Dimensions: 5" H (128mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

#### 2. Top Cover Plate



Dimensions: 2 1/2" H (64mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

#### 3. Deck Choice #1 - 6" Internal Chamber Height



Exterior Dimensions: 13 5/8" H (347mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

Interior Dimensions: 6" H (153mm) x 56"W (1420mm) x 30" D (762mm)

#### 4. Deck Choice #2 - 8" Internal Chamber Height



Exterior Dimensions: 15 5/8" H (397mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

Interior Dimensions: 8" H (203mm) x 56"W (1420mm) x 30" D (762mm)

#### 5. Deck Choice #3 - 10" Internal Chamber Height



Exterior Dimensions: 17 5/8" H (447mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

Interior Dimensions: 10" H (253mm) x 56"W (1420mm) x 30" D (762mm)

#### 6. Deck Choice #4 - 12" Internal Chamber Height



Exterior Dimensions: 19 5/8" H (497mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

Interior Dimensions: 12" H (303mm) x 56"W (1420mm) x 30" D (762mm)

#### 7. Base Plate



Dimensions:

2 1/2" H (64mm) x 73"W (1854mm) x 46 1/2" D (1181mm)

#### 8. Standard Legs with Casters



Dimensions:

**One Deck:** 33" H (838mm) x 73"W (1854mm) x 37 1/2" D (952mm)

**Two Deck:** 24" H (610mm) x 73"W (1854mm) x 37 1/2" D (952mm)

**Three Deck:** 21" H (533mm) x 73"W (1854mm) x 37 1/2" D (952mm)

**Four Deck:** 9" H (227mm) x 73"W (1854mm) x 37 1/2" D (952mm)

#### 9. Optional Proofer



Standard Proofer Dimensions (For 1 - 2 Chambers):

32 1/8" H (817mm) x 73"W (1854mm) x 37 1/2" D (953mm)

Shipping Weight: 700 lbs (318 kg)

Low Profile Proofer Dimensions (For 3 Chambers):

24 5/8" H (651mm) x 73"W (1854mm) x 37 1/2" D (953mm)

Shipping Weight: 700 lbs (318 kg)





PROJECT \_\_\_\_\_

ITEM NO. \_\_\_\_\_

NOTES \_\_\_\_\_

MODEL NUMBER: **3 T**

**ELECTRICAL SYSTEM SINGLE PHASE**

Model	Electrical System *ground wire not included						Water & Drain	Capacity (per deck)	
	Volts	Phase	Amps	kW	Hz	Wires		13"x18"	18"x26"
3T1	208	1	40	8.3	50/60	2	1/2" (12)	6	3
	240	1	34						
3T2	208	1	80	16.6	50/60	2	1/2" (12)	6	3
	240	1	70						
3T3	208	1	120	24.9	50/60	2	1/2" (12)	6	3
	240	1	104						
3T4	208	1	160	33.2	50/60	2	1/2" (12)	6	3
	240	1	140						

**ELECTRICAL SYSTEM THREE PHASE**

Model	Electrical System *ground wire not included						Water & Drain	Capacity (per deck)	
	Volts	Phase	Amps	kW	Hz	Wires		13"x18"	18"x26"
3T1	208	3	23	8.3	50/60	3	1/2" (12)	6	3
	240	3	20						
	480	3	10						
3T2	208	3	46	16.6	50/60	3	1/2" (12)	6	3
	240	3	40						
	480	3	20						
3T3	208	3	69	24.9	50/60	3	1/2" (12)	6	3
	240	3	60						
	480	3	30						
3T4	208	3	92	33.2	50/60	3	1/2" (12)	6	3
	240	3	80						
	480	3	40						

