



ICMA-36-E

ELECTRIC ELEMENT

- Two 3 KW incoloy heating elements.
- Independent left and right heating zones maximize function and performance.
- 208 and 240 volts, 3 phase operation

EXTERIOR FEATURES

- Constructed using aluminized steel for maximum heat retention and heat distribution.
- Stainless steel front, sides and top.
- Welded and polished stainless steel seams.
- Mounts over IR and IHR Imperial ranges with mounting accessory.
- Can be wall or counter mounted.
- One year parts and labor warranty.

BROILER RACK

- Chrome plated heavy duty rack.
- Loads and unloads easily.
- Full width, large capacity for high production in peak hours.
- Rack easily lifts out for cleaning.
























CHEESEMELTER

MODEL	DESCRIPTION	DIMENSIONS	CRATED DIMENSIONS	ELEMENTS KW	ELEMENTS NUMBER	SHIP WEIGHT KG	SHIP WEIGHT LBS
ICMA-36-E	CHEESEMELTER	36" W X 17¾" D X 17¼" H (914 X 451 X 438 MM)	38" W X 20" D X 21" H (965 X 508 X 533 MM)	3 KW ea.	2	75	162

ELECTRICAL REQUIREMENTS

MODEL	TOTAL KM	VOLTS	PH	AMPS
	6	208	3	17
ICMA-36-E	6	240	3	14
	6	480	3	7

CLEARANCE REQUIREMENTS

For use only on non-combustible surfaces. Legs are required for counter top installation. Provide 0" clearance from non-combustible surfaces and 8" (203 mm) from combustible surfaces.





OPTIONS AND ACCESSORIES

- Wall mounting kit
- 4" (102 mm) leg kit for counter mounting
- Reinforcement channels to mount on range

