



IHPA-3-36SU

Model Numbers IHPA-2-12SU IHPA-4-24SU IHPA-6-36SU IHPA-8-48SU



LARGE 5" (127 MM) STAIN-LESS STEEL LANDING LEDGE FOR CONVENIENT PLATING.

OPEN BURNERS

- PyroCentric[™] 32,000 BTU (9 KW) anti-clogging burner with a 7,000 BTU/hr. (2 KW) low simmer feature. Two rings of flame for even heating.
- · Burners are anti-clogging and lift-off and separate for easy cleaning.
- · No gaskets or screws.
- · One standing pilot per burner for instant ignition.


GRATES


- Anti-clogging pilot is designed into the grate to shield the pilots from grease and debris.
- Pots slide easily from section to section and onto landing ledge.
- · Grates are cast iron for a long service life.


EXTERIOR FEATURES

- Stainless steel front, sides and landing ledge for cleanability and professional look.
- · Welded and polished stainless steel seams.
- Range Match profile when placed on a refrigerated base or equipment stand.
- · Stainless steel landing ledge is ideal for plating.
- · Control knobs are durable die cast metal for long life.
- Full width, removable crumb tray for easy cleaning.
- 4" (102 mm) heavy duty legs with adjustable feet.
- One year parts and labor warranty.









GAS HOT PLATES - STEP UP









WIDTH	MODEL	OPEN BURNERS			SHIP WEIGHT	
			BTU	KW	KG	LBS
12" (305)	IHPA-2-12SU	2	64,000	19	41	90
24" (610)	IHPA-4-24SU	4	128,000	38	68	150
36" (914)	IHPA-6-36SU	6	192,000	56	114	250
48" (1219)	IHPA-8-48SU	8	256,000	75	145	320

MODEL	DIMENSIONS	CRATED DIMENSIONS		
IHPA-2-12SU	12" W X 31-3/8" D X 14-3/4" H (305 X 797 X 381 MM)	14-1/2" W X 34" D X 17" H (368 X 864 X 432 MM)		
IHPA-4-24SU	24" W X 31-3/8" D X 14-3/4" H (610 X 797 X 381 MM)	26-1/2" W X 34" D X 17" H (673 X 864 X 432 MM)		
IHPA-6-36SU	36" W X 31-3/8" D X 14-3/4" H (914 X 797 X 381 MM)	38-1/2" W X 34" D X 17" H (978 X 864 X 432 MM)		
IHPA-8-48SU	48" W X 31-3/8" D X 14-3/4" H	50-1/2" W X 34" D X 17" H (1283 X 864 X 432 MM)		

Notes: Measurements in () are metric equivalents. Crated Dimensions: 12"h (305). Add 2 ½" (64) to Hot Plate depth and width. Add 4" (102) to height for Step-up

OPTIONS AND ACCESSORIES

- · Stainless steel equipment stands
- 6" (152 mm) casters for equipment stands
- 10" (254 mm) stainless steel wok ring
- · Saute burner head, interchangeable
- Gas shut off valve 3/4" N.P.T
- Quick disconnect and flexible gas hose 3/4" N.P.T

CLEARANCE REQUIREMENTS

Provide 0" clearance from non-combustible surfaces and 8" (203 mm) from combustible surfaces.

MANIFOLD PRESSURE						
NATURAL GAS	PROPANE GAS	MANIFOLD SIZE				
5.0" W.C.	10.0" W.C.	3/4" (19 MM)				



