RANDELL®

Reach-In Single Door Freezer models 2010E

ileach-in Single Door 1166	ZGI IIIOUEIS 2010F
model □ 2010F □ 2010FE □ 2010FEM [☐ 2010FM ☐ 2010FEM-XXXX* ☐ 2010FM-XXXX*
Description: Randell Series 2000 Reach-Inare built for years of efficient, high performance service. The top mounted, expansion valve refrigeration system offers the highest, most consistent performance available while maximizing usable interior space.	model 2010F shown Cnergy ENERGY STAR
Specifications: CABINET EXTERIOR: Cabinet body is constructed of all metal, inside & out. The top, bottom, & back are galvanized steel. Front and sides are available in finishes as listed above. Door and louver are stainless steel and are removable without tools. Unit on 6" casters, front two are locking.	
CABINET INTERIOR: Interior of cabinet is fully coved to meet N.S.F. standard #7. The interior walls, ceiling and door liner are available in either stainless steel or anodized aluminum as listed above. Foamed in place, CFC free urethane insulation. Snap-in A.B.S. breaker strips allow access to condensate heater wires.	Standard Features Continued: C.F.C. Free R-404a Refrigerant Efficient Hot Gas Condensate Evaporator Full Automatic Coil Defrost With Programmable Timer and Safety Switches 8' Cord & Plug Main Power Supply Switch
DOORS: Stainless steel front with either anodized aluminum or stainless steel liner, mounted on heavy duty cam lift hinges with automatic light switch, heavy duty chrome handle, cylinder door lock.	 Self-Closing Cam Lift Hinges with 120° Open Feature (Lifetime Warranty) Automatic Interior Light for door 6" Casters - Factory Mounted (Front two Locking) Cylinder Door Locks
REFRIGERATION: Top mounted condensing unit and evaporator coil, expansion valve system with pressure control, factory tested and balanced to maintain (0° F. to -5° F.) average interior temperature utilizing CFC free 404a refrigerant. Evaporator coil is coated to resist corrosion. Unit supplied with master on/off switch and 8' cord and plug. Access to service points without tools is standard. Provided with full automatic coil defrost with programmable timer	 Polyurethane Insulation Snap-In Magnetic Door Gaskets Condensate Heaters Around All Door Openings 3 Baked Epoxy Coated Wire Shelves With Stainless Steel Support Clips (Adjustable every 1") Fully Coved Interior Meeting N.S.F. Standard #7
and safety switches.	Options & Accessories (Add Suffix "M"):
Finishes: Standard Series Doors/Louver: Stainless steel.	Universal Tray Slides (set of two) Qty Sets 1/2 Doors Solid Qty Location 6" Legs
Exterior Sides: Anodized aluminum. Interior: Anodized aluminum E Series (Add Suffix "E") Cabinet interior, exterior sides,	Extra Interior Shelves Qty
fronts, and doors stainless steel.	☐ Finished Back
Standard Features:	Export Voltage(s) Specify Voltage

• Top mounted Compressor & Evaporator Coil

Exterior LED Temperature Display

Expansion Valve

Digital Control

☐ Blade Locks in Lieu of Cylinder Locks


Refrigeration Type (Add Suffix "R"):


Prison Package


Remote


some models available for -10°F applications, consult factory













TRAYSLIDE CAPACITIES

Universal Pan Slides Model....RIUNIVPS - set of two. For 12 x 20 food pans or 18 x 26 sheet pans.

Maximum capacity of 12" x 20" food pans per full height section: (6) 6" deep pans, (8) 4" deep pans, (18) 2" deep pans.

Maximum capacity of 18" x 26" sheet pans with 2" spacing is (22).

FOR REMOTE MODELS Use same specifications as self-contained models except for:									
Model No.	Rec. H.P.	Rec. BTU/Hr.	Amp.	Ship Wt.					
2010FR solid door	1/2	2120	7	345					

Note: All remote Reach-Income standard on 6" legs in lieu of casters.

SELF-CONTAINED SINGLE SECTION FREEZERS													
Model	L	D	Н	Doors	Cu./Ft.	Shelves	Shelves Sq. Ft.	HP	Volt	Amps	NEMA	BTU Rating	Ship Wt.
2010F solid door	30"	33 1/2"	81.25"	1	24	3	11.75	1/2	115/60/1	9.3	5-15P	2120*	425

*Based on 90° ambient and -10 $^{\circ}$ evaporator.



1055 Mendell Davis Drive, Jackson, MS 39272, 888-994-7636, unifiedbrands.net Information contained in this document is known to be current and accurate at the time of printing/creation. Unified Brands recommends referencing our product line websites, unifiedbrands.net, for the most updated product information and specifications.









