RANDELL®

Upright Reach-In Double Glass Door Freezer models 2021F

Description:

Randell Series 2000 Upright are built for years of efficient, high performance service. The top mounted, expansion valve refrigeration system offers the highest, most consistent performance available while maximizing usable interior space.

Specifications:

CABINET EXTERIOR: Cabinet body is constructed of all metal, inside & out. The top, bottom, & back are galvanized steel. Front and sides are available in finishes as listed above. Doors and louver are removable without tools. Unit on 6" casters, front two are locking.

CABINET INTERIOR: Interior of cabinet is fully coved to meet N.S.F. standard #7. The interior walls, ceiling and door liner are available in either stainless steel or anodized aluminum as listed above. Foamed in place, CFC free urethane insulation. Snap-in A.B.S. breaker strips allow access to condensate heater wires.

DOORS: Glass front with either anodized aluminum or stainless steel liner, mounted on heavy duty cam lift hinges with automatic light switch, heavy duty chrome handle, cylinder door lock.

REFRIGERATION: Top mounted condensing unit and evaporator coil, expansion valve system with pressure control, factory tested and balanced to maintain (0° F. to -5° F.) average interior temperature utilizing CFC free 404a refrigerant. Evaporator coil is coated to resist corrosion. Unit supplied with master on/off switch and 8' cord and plug. Access to service points without tools is standard. Provided with full automatic coil defrost with programmable timer and safety switches.

Finishes:

Standard Series Louver: Stainless steel.
Exterior Sides: Anodized aluminum. Interior: Anodized aluminum
E Series (Add Suffix "E") Cabinet interior, exterior sides
and fronts stainless steel.

Standard Features:

- Expansion Valve
- Digital Control
- Exterior LED Temperature Display
- Top mounted Compressor & Evaporator Coil

model 2021F shown




Standard Features Continued:


- C.F.C. Free R-404a Refrigerant
- Efficient Hot Gas Condensate Evaporator
- Full Automatic Coil Defrost With Programable Timer and Safety Switches
- 8' Cord & Plug
- Main Power Supply Switch
- Self-Closing Cam Lift Hinges with 120° Open Feature (Lifetime Warranty)
- Automatic Interior Light on door
- 6" Casters Factory Mounted (Front two Locking)
- Cylinder Door Locks
- Fully Coved Interior Meeting N.S.F. Standard #7
- Polyurethane Insulation
- Condensate Heaters Around All Door Openings
- 3 Baked Epoxy Coated Wire Shelves Per Section
 With Stainless Steel Support Clips (Adjustable every 1")
- Snap-In Magnetic Door Gaskets


Options & Accessories:


	Universal Tray Slides (set of two) Qty Sets	
	1/2 Doors	
	6" Legs	
	Extra Interior Shelves Qty	
	(maximum of (23) or (20) additional on 1.5" centers-leaves 1" clear) Finished Back	
	Export Voltage(s) Specify Voltage Prison Package	0°F to
Ref	rigeration Type (Add Suffix "R"): Remote	availa for -1 applica cons facto













TRAYSLIDE CAPACITIES

 $\textbf{Universal Pan Slides} \ \textbf{Model....} \textbf{RIUNIVPS} - \textbf{set of two}.$

For 12 x 20 food pans or 18 x 26 sheet pans.

Maximum capacity of 12" x 20" food pans per full height section: (6) 6" deep pans, (8) 4" deep pans, (18) 2" deep pans.

Maximum capacity of 18" x 26" sheet pans with 2" spacing is (22).


FOR REMOTE MODELS Use same specifications as self-contained models except for:										
Model No.	Rec. H.P.	Rec. BTU/Hr.	Amp.	Ship Wt.						
2021FR solid door	3/4	3520	9	570						

Note: All remote Upright come standard on 6" legs in lieu of casters.

	SELF-CONTAINED SINGLE SECTION FREEZERS												
Model	L	D	H	Doors	Cu./Ft.	Shelves	Shelves Sq. Ft.	HP	Volt	Amps	NEMA	BTU Rating	Ship Wt.
2021F solid door	55"	33 1/2"	81.25"	2	46.08	6	26	2/3	115/60/1	15.4	5-20P	3520*	620

*Based on 90° ambient and -10° evaporator.







1055 Mendell Davis Drive, Jackson, MS 39272, 888-994-7636, unifiedbrands.net Information contained in this document is known to be current and accurate at the time of printing/creation. Unified Brands recommends referencing our product line websites, unifiedbrands.net, for the most updated product information and specifications. À City Discount