

Outperform every day."

Project:

Item Number:

Quantity:

VACUUM PACKING MACHINE WITH DUAL 16" SEALING BARS



Vacuum Packing Machine with Dual 16" Sealing Bars

DESCRIPTION

The Vollrath Vacuum Packing Machine with Dual 16" Sealing Bars provides versatile, high-quality vacuum packing in a small footprint tabletop machine. Liquid Sensor Control helps ensure moist or liquid products can be packed without degrading the product or damaging the machine. Additional features such as Vacuum Plus and Soft-Air enable the user to adjust performance to pack a wide variety of products.

Preset programs can be customized for simple operation and consistent outcomes.

Packing cycle begins when the lid is closed and ends when the lid automatically opens.

ITEMS

Item No. Model No. Description

40833 VP16 Vacuum Packing Machine with Dual 16" Sealing Bars

FEATURES

- · Busch rotary vacuum pump
- · Stainless steel exterior
- Deep drawn stainless steel vacuum chamber with round corners
- Transparent, soft-open lid for monitoring functions
- Dual sealing bars accommodate multiple bags up to 16" (40.6 cm) wide
- Double seals for extra secure bags
- Sealing bars easily remove without tools for cleaning and maintenance
- · Includes three insert plates for packing small products
- Includes incline plate for packing liquids and fine powders
- Maximum vacuum is 99.8% (2 m bar)
- Set vacuum function by time or sensor control (% pressure)
- Ten programs include Liquid Control, Soft-Air and Vacuum Plus functions
- Soft-Air reduces damage to delicate foods or the bag
- Liquid Control detects the boiling point, stops the vacuum and advances to the next step to reduce cycle time, produce a better quality product and save the pump from taking on liquids
- · Vacuum Plus enables air trapped within a product to escape
- Pump Conditioning program removes moisture and debris from pump
- Two sealing cylinders provide optimal pressure to deliver high-quality seals
- Maintenance reminder
- Includes 4" (10.2 cm) optional legs
- Includes maintenance kit with oil, lid gasket, silicone bar, Teflon® tape and sealing wire
- 6 ft. (182. 9 cm) cord with plug
- 2 year warranty

IMPORTANT

- Requires 6" (15 cm) clearance on all sides
- Requires a minimum clearance of 30" (76.2 cm) above the machine
- This machine is not designed for continuous use. Intended maximum use is five hours per day.
- Requires 15 second rest between packing cycles.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to www.Vollrath.com.

Approvals	Date				





Due to continued product improvement, please consult www.vollrathco.com for current product specifications.





www.vollrath.com


The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or 920.459.6573

VACUUM PACKING MACHINE WITH DUAL 16" SEALING BARS

DIMENSIONS (Shown in inches (cm)








Side View Top View

SPECIFICATIONS

	Dimensions IN (CM)									
Item No.	Chamber (W x D x H)	Maximum Product Height	Volts	Amps	Hz	Pump Capacity	НР	Plug	Weight LB (KG)	
40833	16 ¹³ / ₁₆ x 16½ x 5 (42.7 x 41.9 x 12.7)	7½ (19.1)	120	13	60	25 m3/hr	1.3	NEMA 5-20P	136.7 (62)	







The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830

Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or 920.459.6573 Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462

© 2015 The Vollrath Company L.L.C.

Form Number 36017

2/16/15 Printed in USA