

Mobile Work Tables



Custom Sizes Available

Under-Counter/Half Height

ALUMINUM OR STAINLESS CONSTRUCTION

Item No. _____

Quantity _____

Job Name _____

Spec No. _____

Construction: Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. Lifetime guarantee against rust.

Tray Slides: Slides are 1" X 1 1/2" extruded aluminum angle heli-arc welded to frame. Bottom load ledge design.

Frame and Cross Supports: Vertical and horizontal frame sections are 1" extruded aluminum tubing.

Casters: Stem type 5" diameter, full swivel design. Non-marking polyurethane wheel. Caster stems are securely bolted to frame to facilitate replacements.

Pan Accommodations: See tabulation.

ALUMINUM		REGULAR 1/2 SIZE			
Model	Wt.	Spacing/Capacity	H	W	D
425A	24	FL3"/9 Pans	36"	20 1/2"	26"
426A	22	FL4"/7 Pans	36"	20 1/2"	26"
427A	20	FL5"/5 Pans	34 1/2"	20 1/2"	26"
428A	22	SL3"/9 Pans	36"	28 1/2"	18"
429A	21	SL4"/7 Pans	36"	28 1/2"	18"
UNDER COUNTER					
430A	23	FL3"/8 Pans	32"	20 1/2"	26"
431A	21	FL4"/6 Pans	32"	20 1/2"	26"
432A	20	FL3"/5 Pans	23"	20 1/2"	26"

STAINLESS		REGULAR 1/2 SIZE			
Model	Wt.	Spacing/Capacity	H	W	D
425S	37	FL3"/9 Pans	36"	20 1/2"	26"
426S	34	FL4"/7 Pans	36"	20 1/2"	26"
427S	30	FL5"/5 Pans	34 1/2"	20 1/2"	26"
428S	33	SL3"/9 Pans	36"	28 1/2"	18"
429S	30	SL4"/7 Pans	36"	28 1/2"	18"
UNDER COUNTER					
430S	36	FL3"/8 Pans	32"	20 1/2"	26"
431S	32	FL4"/6 Pans	32"	20 1/2"	26"
432S	31	FL3"/5 Pans	23"	20 1/2"	26"

KNOCK DOWN					
Model	Wt.	Spacing/Capacity	H	W	D
425AKD	22	FL3"/9 Pans	36"	20 1/2"	26"
426AKD	21	FL4"/7 Pans	36"	20 1/2"	26"

Options
/011 Caster Brakes

Work Top Options
/A Aluminum
/S Stainless
/P Polytop



425A



425A/P



Angle Slides Hold Pans Securely On Bottom


Work Top Options

- /A Aluminum
- /S Stainless
- /P Polytop

FL - Front Load



SL - Side Load



CHANNEL
MANUFACTURING, INC.

55 Channel Drive • Port Washington, NY 11050-2216
8891 NW 102nd Street • Medley, FL 33178
Tel: 516-944-6271 • Fax: 516-944-0625
Toll Free: 866-712-7283
www.channelmfg.com • Email: sales@channelmfg.com