

STAINLESS STEEL

HAND SINKS 🕦 **STANDARD**


SPLASH MOUNTED FAUCETS







7-PS-68



Keyhole Bracket for easier installation and greater stability.







7-PS-67





7-PS-20-NF Faucet omitted

FEATURES:

One piece Deep Drawn sink bowl design.

Sink bowl is 10" x 14" x 5".

7-PS-45 sink bowl size is 16" x 20" x 8".

7-PS-49 sink bowl size is 16" x 14" x 8".

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

Keyhole wall mount bracket.

Stainless steel basket drain 1-1/2" IPS.

Specific Features:

7-PS-20-NF deck mounted faucet ommitted.

7-PS-50 features lever operated drain and built-in overflow with plastic overflow tube and spring clamps. P-Trap is 1 1/2".

7-PS-54 features P-Trap only. P-Trap is 1 1/2".

7-PS-20 4" O.C. deck mounted centerset faucet furnished with aerator.

7-PS-50 & 7-PS-60 4" O.C. splash mounted gooseneck faucet, chrome plated & furnished with aerator.

7-PS-45 Same as above plus 2 Support Brackets (Hardware Included).

7-PS-67 features lever operated drain.

7-PS-68 4" O.C. splash mounted gooseneck faucet with Wrist Handles, chrome plated & furnished with aerator.

SINGLE HOLE PUNCH Faucet omitted



DOUBLE HOLE PUNCH

Faucet omitted



CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish. Die formed Countertop Edge with a No-Drip offset.

One sheet of stainless steel - No Seams.

LARGE SIZE SINK BOWLS



7-PS-71



MATERIAL:

Heavy gauge type 304 series stainless steel. Wall mounting bracket is Galvanized and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

MECHANICAL:

Faucet supply is 1/2" IPS male thread hot and cold.

Standard Faucet conforms to NSF 61 Standard 9. Faucets Are AB1953 Lead Free Compliant.

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at www.advancetabco.com



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

NEW YORK Fax: (631) 242-6900

GEORGIA Fax: (770) 775-5625

TEXAS Fax: (972) 932-4795 **NEVADA**


Fax: (775) 972-1578

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL





ADVANCE TABCO is constantly engaged in a program of improving our products. Therefore, we reserve the right to change specifications without prior notice.