

7512

Value Series Slicer

Univex Corporation

#### WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity

# 7512 Value Slicer

### Model:

> 7512: 1/2hp Manual Slicer





\*NEW Low Friction Blade comes standard with slicer!

CERTIFIED BY NSF INTERNATIONAL TO MEET AND EXCEED THE NSF/ANSI 2012 STANDARDS

#### **Features:**

- Medium duty, moderate volume slicer
- Maximum duty 6 hours a day
- Capable of slicing moderate amounts of cheese
- Unique drip tray fence redirects liquids away from controls and operator towards distinctive concave base casting for easy cleaning
- Ergonomic comfort design operation
- Powerful 1/2 hp motor standard
- Adjustable slice thickness from 0 to 7/8"
- Easily removable sharpener for cleaning
- Quick and simple disassembly of carriage and feed grip for easy and thorough cleaning
- Sanitary polished and anodized aluminum construction
- Permanently mounted protective edge guard for operator safety
- Heavy duty 3-1/2 lb gravity fed grip

12" Precision slicing German hollow ground blade
Unique smooth curve transitions to redirect
liquids away from controls and operator
Easily detachable carriage for easy cleaning

## **Optional Accessories:**

- Stainless steel blade
- Heavy duty clear plastic cover
- Stainless steel vegetable chute
- Sturdy stainless steel stand

## Warranty:

• One year, on-site parts and labor



Univex Corporation www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249


Printed in U.S.A. REV 1 01/2017 LH-575




# **Value Series Slicer**

**7512** 







Controls: Manual slice thickness knob, push button on/off,

attached blade sharpener

Drive Assembly: Belt driven

Blade diameter: 12" (30.4cm) razor sharp blade

Blade RPM: 345 RPM

Maximum slice thickness: .875" (2.2cm)

Maximum product size: Rectangular: 9.25" x 7.5" (24.5cm x 19cm)

Square: 7.5" x 7.5" (19cm x 19cm)

Round: 8" (20.3cm)

Construction: Anodized, cast aluminum body for durability

and stunning looks

Nema #: 5-15-P

Electrical Information (60Hz)						
	Voltage	Phase	Amps	RPM	hp(kW)	
Standard Voltage	115	1	4.0	1680	1/2 (.37)	
Optional Voltage	208-240	1	2.5	1680	1/2 (.37)	

Carriage Stroke	
11" (28cm)	

Shipping Information				
Net Weight Shipping Weight		Overall Shipping Dimensions		
98.1lbs. (44.5Kg)	106lbs. (48.1Kg)	23" (55.9cm) H x 20" (50.8cm) W x 27" (66cm) D		



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249