

DROP-IN DISPENSERS for SQUARE and OVAL PLATES

Square or Oval Plate Dispensers provide a unique fit for your modern-shaped plates.

- Adjusting height level is easy and convenient. Simply detach and attach springs as needed without tools
- Easy glide design is non-stick for smooth operation
- Choose the type of dispenser that best fits your needs:
 - **Open model** for economic dispensing
 - **Shielded** to protect against contaminants and plate chipping
 - **Heated** with adjustable thermostatic control to maintain food safe temperatures (thermostat min- 100° F, max- 175° F)
- Stainless steel material is durable and easy to clean and sanitize

- Regular height models have 25" (635) stacking height capacity
- Model 968 has Adjust-A-Fit® diameter hand adjustment for flexibility in varying platter sizes
- Overall size is 15 1/3"W x 17 1/2" L x 28 1/4" H (389 W x 445 L x 718" H)

ELECTRICAL SPECIFICATIONS		
450 W	3.8 A	120 V
208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.		



Open Model #S4010

Adjust-a-Fit® Model #968

Regular Model #V4010

ACCESSORIES (PAGE 79):

- Stainless Steel Dish Covers



Ships in: **21** days or less!

REGULAR SQUARE PLATE DISPENSERS – DROP-IN | STAINLESS STEEL

Open Model	Case Weight Lbs. (Kg)	Shielded Model	Case Weight Lbs. (Kg)	Heated Model	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)	Accommodates Plate Sizes
S4006	12 (5.4)	-	-	-	-	3.9 (.11)	5 to 5-3/4" (127 to 146)
S4007	13 (5.9)	-	-	-	-	3.9 (.11)	6-1/4" to 7-1/2" (159 to 191)
S4009	16 (7.2)	S5009	23 (10.4)	S6009	26 (11.8)	6.9 (.19)	8-1/2" to 9-1/4" (216 to 235)
S4010	17 (7.7)	S5010	24 (10.9)	S6010	28 (12.7)	6.9 (.19)	9-1/2" to 10-1/4" (241 to 260)
S4011	18 (8.1)	S5011	26 (11.7)	S6011	30 (13.5)	6.9 (.19)	10-1/2" to 11-1/4" (267 to 286)
S4012	19 (8.6)	S5012	29 (13.2)	S6012	32 (14.5)	6.9 (.19)	11-1/2" to 12" (292 to 309)

OVAL PLATE DISPENSERS - DROP-IN | STAINLESS STEEL

Open Model	Case Weight Lbs. (Kg)	Shielded Model	Case Weight Lbs. (Kg)	Heated Model	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)	Accommodates Plate Sizes
Adjust-A-Fit®							
968	24 (10.9)	-	-	970	41 (18.6)	7 (.20)	8-3/4" x 9-3/4" to 11-3/4" x 13-1/2"
Regular							
V4010	18 (8.2)	V5010	26 (11.8)	V6010	30 (13.6)	7.1 (.18)	6-3/4" x 9-3/4" to 7-3/4" x 10-1/2"
V4011	20 (9.1)	V5011	28 (12.7)	V6011	32 (14.5)	7.1 (.18)	8" x 10-3/4" to 8-1/2" x 11-1/2"
V4012	22 (10.0)	V5012	30 (13.6)	V6012	34 (15.4)	7.1 (.18)	8-3/4" x 11-3/4" to 9-1/4" x 12-1/2"
V4013	24 (10.9)	V5013	32 (14.5)	V6013	36 (16.3)	7.1 (.18)	9-1/2" x 12-3/4" to 10-1/4" x 13-1/2"
V4014	27 (12.2)	V5014	35 (15.9)	V6014	39 (17.7)	7.1 (.18)	9-3/4" x 13-3/4" to 10-3/4" x 14-1/2"

Measurements in () denote metric millimeters, unless otherwise specified. Heated Models include 5' (1524) cord with 5-15R NEMA twist lock plug. Thermostat minimum 100°F - maximum 200°F. All models can ship FedEx Ground or UPS. For Ring Cut Out Information and Top Ring Size, please contact factory. Height to top rim is 27-3/4" (705) for open models, 28" (711) for shielded and heated models.

HEIGHT AND CUT OUT INFORMATION – SQUARE DISPENSERS

Open Models	Height to Ring	Shielded/Heated Models	Height to Ring	Flange L x W	Counter Cut Out Size
S4006	27-3/4" (705)	-	-	9-1/8" x 9-1/8" (232 x 232)	8-1/16" x 8-1/16" (204 x 204)
S4007	27-3/4" (705)	-	-	10-7/8" x 10-7/8" (276 x 276)	9-13/16" x 9-13/16" (249 x 249)
S4009	27-3/4" (705)	S5009, S6009	28" (711)	12-1/2" x 12-1/2" (318 x 318)	11-1/2" x 11-1/2" (292 x 292)
S4010	27-3/4" (705)	S5010, S6010	28" (711)	13-1/2" x 13-1/2" (343 x 343)	12-1/2" x 12-1/2" (317 x 317)
S4011	27-3/4" (705)	S5011, S6011	28" (711)	14-1/2" x 14-1/2" (368 x 368)	13-1/2" x 13-1/2" (343 x 343)
S4012	27-3/4" (705)	S5012, S6012	28" (711)	15-3/8" x 15-3/8" (390 x 390)	14-1/3" x 14-1/3" (364 x 364)

For counter cut out information for drop-in oval dispenser models, refer to product specification sheet SL-1V.