



**Model #AUC-27**

**Standard Features – Undercounter Refrigerator Model #AUC-27**

- Environmentally-safe R290 refrigerant
- 430 series stainless steel exterior
- Painted aluminum interior
- Foamed-in-place polyurethane insulation
- One epoxy-coated shelf accommodates up to 90 lb.
- Environmentally-safe R290 refrigerant
- Temperature range of 33°F - 40°F
- Digital temperature controls
- 115V; 1/6 HP
- ETL listed. Conforms to UL STD. 471, Certified to CSA STD. C22. 2No.120
- Conforms to NSF/ANSI STD. 7

**Construction**

Exterior Material	430 Stainless Steel
Interior Material	Painted Aluminum
Insulation Material	Foamed-In-Place Polyurethane
Shelf	(1) 21-7/8 x 17-3/4 epoxy-coated steel
Casters	(4) 4" casters for mobility

**Dimensions**

Exterior Dimensions	27"W x 29-1/2"D x 35-1/4"H
Interior Dimensions	22-1/4"W x 22-7/8"D x 23-1/2"H
Shipping Dimensions	29-3/4W x 32-1/4"D x 38-1/2"H
Working Height	35-1/4
Net Volume	5.5 cu. ft.
Net Weight	159 lb.
Gross Weight	202 lb.

**Cooling**

Temperature Range	33°F-40°F
Refrigerant	R290
Max. Ambient Temperature	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/6

**Electrical**

Voltage	115
Amps	1.9
Hz	60
Phase	1
Plug Type	NEMA-5-15P
Electrical Cord Length	84"



Parts & Labor

Compressor

**PLAN VIEW**

Front View

Side View

Top View

