

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Hot Food Tables, open base design, model ______. Top and body to be heavy gauge type 430 stainless steel, with top and water pan removable for cleaning or replacement. All top openings sized to accommodate 12" x 20" steam table pans. Water pan to be all-welded 20/304 stainless steel, complete with 1½" diameter brass drain. Burners are straight flow tubular type with energy-saving design for quick starts (15,000 BTU burner on 2- and 3-well openings, 30,000 BTU burner on 4-, 5-, and 8-well openings) and pressure regulator. ½" NPT pipe connection on right side. Polycarbonate 8" wide cutting board and stainless steel dish shelf provided. Legs to be 1½" O.D. galvanized tubing with galvanized adjustable undershelf, and adjustable non-marking plastic bullet feet.



#AW I 3-NG unit with optional Flex-Master® Overshelf System*

Options / Accessories

- Bolted-in undershelf
- ☐ Tray slides/shelf
- ☐ Rolltop cover
- Serving shelf
- ☐ Top adapters
- □ Food pans/insets
- ☐ AutoFill® automatic water fill system

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

Gas Water Bath Steam Tables— Open Base

MODELS:

□ AWT2-NG	☐ AWTP4-NG	☐ ASWT2-NG	□ ASWTP4-NG
□ AWTP2-NG	☐ AWT4-NG-1	□ ASWTP2-NG	□ ASWT4-NG-1
□ AWT3-NG	☐ AWTP4-NG-1	☐ ASWT3-NG	□ ASWTP4-NG-
□ AWTP3-NG	☐ AWT5-NG	☐ ASWTP3-NG	□ ASWT5-NG
□ AWT4-NG	☐ AWTP5-NG	□ ASWT4-NG	□ ASWTP5-NG

Models listed are units with natural gas. For units with liquid propane, replace suffix "-NG" with "-LP". Example: AWT3-LP

Construction

- Table body and top constructed of highly polished 20 gauge 430 series stainless steel.
- Top has openings sized to accommodate 12" x 20" (305 x 508mm) food pans.
- Poly cutting board 8" (203mm) wide and ½" (32mm) thick is mounted on stainless steel brackets located on control side of unit
- Cutting board and stainless steel dish shelf are standard on all models.
- Legs are 1%" (42mm) O.D. galvanized tubing fitted with adjustable, non-marking plastic feet.
- Undershelf constructed of galvanized steel.

Water pan

• 20 gauge 304 stainless steel all-seamless construction, complete with 1½" (38mm) diameter brass drain.

Burner assembly

- Constructed of aluminized steel with straight flow energysaving design for quick startup.
- 15,000 BTU burner on 2- and 3-opening models; 30,000 BTU burner on 4-, 5-, and 8-opening models.
- ½" (13mm) N.P.T. pipe connection is on right side.
- · Available in LP gas.

Optional safety pilot

Certifications / Approvals

New York MEA 318-84-E

 AGA design certified, complete with high performance cast aluminum automatic shut-off valve and pressure regulator.

AUTOQUOTES




EG30.12 Rev. 03/12

^{*} See Catalog Sheet #EG30.18 for more information on Flex-Master® overshelves



Item No.:	
Project No.:	
S.I.S. No.:	

Gas Water Bath Steam Tables—Open Base




	l	/ ٧٧١١	HSIU	PPER			
-5 ¹ / ₄ " 33mm		<u>/</u>					5" 127mm GAS CONNECTION 1/2" NPT
			FRON	IT VIEV	/		
			111011	, v,_v	•		
	-	3-WEL	L MO	IGTH_ DEL S	HOWN	•	1¹/₄" 32mm


FRONT VIEW	
LENGTH 3-WELL MODEL SHOWN	_1¹/₄" 32mm
4.5	9 ⁹ / ₁₆ " 243mm
H O H	34 ¹ / ₂ " 876mm
	15" 381mm
6" 152mm	71/ ₂ " 191mm
T	191mm
TOP VIEW	

3-well

	Dimension a
2 well	8" (203mm)
3 well	15½" (294mm)
4 well	15½" (294mm)
5 well	23" (584mm)

Note: models #AWT4-NG-1 and AWTP4-NG-1 are provided with (2) 12" x 20", (2) 61/2" round openings, and (4) 8½" round openings. See "8-well" line art below.





5-well						

WITH gal vanized l egs & under s Hel f model #	WITH sTainless sTeel legs & under sHelf model#	description	# of top openings	ler in.	ngth mm	wei Ibs.	ght kg
AWT2-NG	ASWT2-NG	natural gas	2	33"	838	94	42.6
AWTP2-NG	ASWTP2-NG	natural gas, with safety pilot	2	33"	838	96	43.5
AWT3-NG	ASWT3-NG	natural gas	3	48"	1219	125	56.7
AWTP3-NG	ASWTP3-NG	natural gas, with safety pilot	3	48"	1219	130	59.0
AWT4-NG	ASWT4-NG	natural gas	4	63½"	1613	146	66.2
AWTP4-NG	ASWTP4-NG	natural gas, with safety pilot	4	63½"	1613	151	68.5
AWT4-NG-1	ASWT4-NG-1	natural gas	8	63½"	1613	146	66.2
AWTP4-NG-1	ASWTP4-NG-1	natural gas, with safety pilot	8	63½"	1613	151	68.5
AWT5-NG	ASWT5-NG	natural gas	5	79″	2007	183	83.0
AWTP5-NG	ASWTP5-NG	natural gas, with safety pilot	5	79"	2007	189	85.7

4-well

To order units with liquid propane in place of natural gas, replace suffix "-NG" with "-LP". Example: AWT3-LP

FLEX-MASTER® Overshelf Kits

2-well

Both kits include two 16/304 overshelves and four 30" (762mm) posts. Add suffix specified to order kit (example: DHT2-120-FMU), or design your own using standard components from EG30.18.

description	add suffix
10" (254mm) overshelves	-FM
15" (381mm) overshelves, plus one ladle rack	-FMU

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2012 by Eagle Group

Rev. 03/12