

ACR46GL



31.5" x 19.5" x 22.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, with stainless steel trimmed glass door, frost-free with an internal fan, external digital controls and thermometer, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

External temperature readout of the current and high/low temperatures

Product Features:

Vaccine refrigerator	Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage
ADA compliant	Sized just under 32" high to allow installation under lower ADA compliant counters
Built-in capable	Front-breathing system allows the unit to be installed under cabinets with minimum clearance
Slim 20" width	Full 2.65 cu.ft. capacity inside conveniently slim footprint
Commercially listed	ETL-S listed to ANSI-NSF-7 commercial standards
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines

ACR46GL Specifications:

Overview	
Height of Cabinet	31.5" (80 cm)
Width	19.5" (50 cm)
Depth	22.75" (58 cm)
Depth with Handle	25.0" (64 cm)
Depth with door at 90°	41.0" (104 cm)
Capacity	2.65 cu.ft. (75 L)
Defrost Type	Frost-Free
Door	Glass/SS
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	89.0 lbs. (40 kg)
Shipping Weight	99.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101059426
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	0.99oz.
High Side PSI	270.0
Low Side PSI	105.0
Level Legs Qty	4
Interior Light	Yes
Temperature Range	2° to 8°C
Dimensions	
Interior Height	21.25" (54 cm)
Interior Width	15.0" (38 cm)

Interior Depth	16.13" (41 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	15.0" (38 cm)
Compressor Step Depth	4.75" (12 cm)

