



Stainless design.
Stellar performance.
Superior value.

Project name: _____

Location: _____

Item #: _____ QTY: _____

Model #: _____

AUC48F FREEZER

TWO DOOR UNDER-COUNTER WORK TOP FREEZER



AUC48F

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full two year parts and labor warranties and a five year compressor warranty.
- ▶ Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- ▶ All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.



COMMERCIAL FREEZERS & REFRIGERATORS

Division of Broich Enterprises, Inc. 7550 Market Place Dr Eden Prairie, MN 55344
952-941-2270 Fax: 952-941-3066 www.arcticairco.com info@arcticairco.com



AUC48F FREEZER

TWO DOOR UNDER-COUNTER WORK TOP FREEZER

Solid door construction with foamed-in-place recessed handle.

Magnetic door gaskets are removable and replaceable without tools.

Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet walls are constructed of white epoxy coated steel liner with full hi-level stainless steel covered corner floor.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.



All units come standard with heavy-duty worktop surface.

Vaulted self closing doors that remain open at 90 degrees.

Self contained capillary tube system using environmentally friendly R290 Hydrocarbon gas.

Easy to mount plate casters (two lockable) are standard with all units.

▶ Tested to NSF Standard 7 requirements for open food storage.

▶ Standard with full two year parts and labor warranties and a five year compressor warranty.

Electronic thermostat with external digital LED display for accurate control and easy reading.

Two adjustable, heavy-duty epoxy coated wire shelves.

STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

Model Number	External Dimensions			Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	HP	AMPS	REF	NEMA Plug	Crate Weight
	Width	Depth	Height*										
AUC48F	48.25"	30"	35.625"	2	2	10.1	-10°F to 10°F	8'	1/3	2.1	R290	5-15P	280Lbs

Depth with door open 90° = 52.875"

*Height includes 3" for casters

Height with worktop removed = 34.125"

