
GREASE TRAPS

Steel Grease Traps







BK-GT - Carbon Steel Grease Traps

- Constructed of 11 ga Carbon Steel w/
- Corrosion Resistant Coating
- Non-Skid Deck Plate

BK

RESOURCES

- Removable Baffles for Ease of Maintenance
- Main Body of Grease Trap Suspended Above Floor to Avoid Corrosive Environment and Extend Life
 No Hub Connections
- T-Vent Provided
- Designed for removing and isolating F.O.G. (Fat, Oil, Grease) from wastewater wherever Food is Prepared

Part Number	GPM Capacity	Grease Cap (lbs.)	Α	В	C	D	Width	
BK-GT-8	4	8 lbs.	14 ^{1/8} "	11 ^{1/4} ″	7 ^{1/2} "	2″	10 ^{1/2} "	
BK-GT-14	7	14 lbs.	16 ^{1/8} "	12 ^{1/8} "	81/8″	2″	131/2″	
BK-GT-20	10	20 lbs.	201/8"	12 ^{1/8} "	8 ^{1/8} ″	2″	141/2″	
BK-GT-30	15	30 lbs.	201/2"	13 ^{7/8} "	10 ^{3/8} "	2″	16″	
BK-GT-40	20	40 lbs.	221/2"	15″	11 ^{1/2} "	3″	16″	
BK-GT-50	25	50 lbs.	241/2″	16 ^{1/2} "	12″	3″	17 ^{1/2} "	
BK-GT-70	35	70 lbs.	281/2"	19 ^{1/2} "	141/8″	3″	18″	
BK-GT-100	50	100 lbs.	301/2″	21 ^{1/2} "	16 ^{1/8} "	4″	221/4″	

• BK-GT-8, BK-GT-14, BK-GT-20, BK-GT-30 Listed by IAPMO R&T File #C-7235

• BK-GT-40, BK-GT-50, BK-GT-70, BK-GT-100 Listed by IAPMO R&T File #6728

What Size Grease Trap Do I Need?

Use this formula or calculation to find the right size grease trap for your kitchen setup.*

1.	Length X Width X Depth of your bowls (All Total. Example: a 3 Compartment Sink - add up each compartment LxWxD for a total)	+
2.	Multiply that number by the number of bowls (Example: a 3 Compartment Sink, multiply by 3)	X
3.	Divide by 231 (This gives you contents in gallons.)	•
4.	Multiply by .75 (This gives you grease capacity in lbs.)	Х
5.	Look up capacity (lbs.) to find grease trap model you will need	TOTAL

* Always refer to Local Codes.

Thanks to The Plumbing & Drainage Institute for this formula.