
60.0" N 24"



MODEL INFORMATION							
TYPE	DIMENSIONS			CFM SI	WEIGHT		
	LENGTH	WIDTH	HEIGHT	EXHAUST PLENUM	SUPPLY PLENUM	105 lbs	
'	60"	30"	24"	1250 @ 0.5 ESP	N/A	103 105	

OBS.: Installing contractor have the responsability to ensure hood cleareance from limitedcombustible and combustible materials is compliant with local code requirements.

STANDARD COMPONENTS						
MOUNTING BRACKET 12-GAUGE GALVANIZED	Grease Drain	Grease Cup Stainless Steel NSF	Grease Filter Stainless Steel UL 1046			
QTY QTY QTY		QTY	Length	Height		
			0	16"	20"	
4	1	1	3	20"	20"	
			0	25"	20"	


SUGGESTED COMPONENTS							
Б	Exhaust Collar		Collar	Light Fixture	Shipping Crate Dimensions (in) and Weight (lb)		
16-Go	16-Gauge Cold Rolled		/A	UL Listed (Included Component)	Length:	64"	
	Build	14/70			Width:	34"	
QTY	Size	QTY	SIZE	QTY	Height:	32"	
1	10.5" x 10.5"	N/A	N/A	1	Weight:	155 lbs	

CSS30-5

STAINLESS STEEL EXHAUST HOOD N.S.F. LISTED. CONFORMS TO NFPA96

Hood Constructed with continuous liquid-tight weld in conformance to IMC 2024 507.2.5.

Hood material: 18 Gauge 430 STAINLESS STEEL (#3 polish) where exposed.




IMPORTANT:

- 1- Drawing presented shows a typical overview of a Hood system installation, and is not intended to be used for permitting purposes.
- 2- It is the responsibility of the installing contractor to assure that the hood, grease duct and fire suppression system are installed in compliance with NFPA17A, NFPA70, NFPA72, NFPA 96, IMC, state and local codes.
- 3- The hood drawing presented on this document may vary based on which optional components were installed upon the client's request.
- 4- It is the responsibility of the installing contractor to observe field dimensions required based on hood spec, ductwork and options installed.

PO BOX 47607 - ATLANTA, GA 30360 PHONE: 770.936.0770 - www.superiorhoods.com			CSS30-5				
			MODEL CSS30 STANDARD SUBMITTAL SHEET				
APPROVED			CODE		DWG NO		REV
CHECKED							01
DRAWN	PRODUCTION	2025	SCALE: 1:34	WEIG	HT: 105 lbs	SHEET: 1/	2


PROFILE VIEW




ITEM	DESCRIPTION
Α	Exhaust Fan
В	Exhaust Curb 3" Tall Typ.
С	Exhaust Riser (Sold Separately)
D	UL 1046 Approved Stainless Steel Grease Filter
Е	Grease Drain Channel
F	Removable Grease Cup not to exceed 1 Gal. Cap
G	Electrical Box (Sold Separately)
Н	UL Approved Light Fixture (Sold Separately)
	Mounting Bracket Assembly

Mounting Bracket Assembly Recomended:

- Threaded Rod not smaller than 3/8"





Superior Hoods
PO BOX 47607 - ATLANTA, GA 30360
PHONE: 770.936.0770 - www.superiorhoods.com

PROJECT CSS30-5

TITLE

TYPICAL HOOD SYSTEM INSTALLATION

APPROVED CODE CHECKED

DWG NO REV 01

DRAWN PRODUCTION 2025 SCALE: 1:17

SHEET: 2/2