

Standard Features, Benefits & Options

CONSTRUCTION: 30", 44", 58" & 72" wide models available. Easy cleaning, corrosion resistant stainless steel finish. Stainless steel legs and undershelf. $\frac{5}{8}$ " thick x 7" poly cutting board. Adjustable leveling bullet feet. Shipped KD.

CONTROLS: ³/₄" rear gas connection, brass gas valves, automatic standing pilots, pressure regulator and cool to the touch control knobs.

BURNERS: Brass burners each rated at 3,100 BTU's, 1 burner for each well.

TESTING: Optimal pressure is 5" WC for natural gas, 10" WC for propane. ETL design & ETL Sanitation (ANSI-NSF4) certified.

Model #	Crated dimensions W x D x H inches centimeters	Burners Total BTU	Net Wgt. Ibs./kg.	Gross Wgt. Ibs./kg.
CCGST-2	40 x 32 x 20 101 x 81 x 51	2 6,200	86/39	101/46
CCGST-3	54 x 32 x 20 136 x 81 x 51	3 9,300	137/62	160/72
CCGST-4	69 x 32 x 20 176 x 81 x 51	4 12,400	192/87	218/99
CCGST-5	81 x 32 x 20 206 x 81 x 51	5 15,500	240/109	276 / 125



Comstock-Castle Stove Co. • 119 W. Washington St. • Quincy, IL. 62301 Tel.: 217-223-5070 • Fax.: 217-223-0007 • Web: <u>www.castlestove.com</u>

