

PROJECT	
ITEM #	
QUANTITY	DATE
APPROVAL	

KCTS

Mobile Tray and Silver Stands

Short Form Specifications

Exterior Body is seamless, one-piece molded fiberglass, having perfectly smooth exterior surface with all corners fully rounded. The fiberglass reinforced polyester (F.R.P.) is molded with permanent color. Stress points are internally reinforced.

Exterior top is constructed of 14-gauge stainless steel, welded, ground and polished into one integral unit. Top is fabricated with square exterior corners. Top has area for silverware with stepdown for trays.

Casters; unit is mounted on 5" (12.7cm) diameter swivel casters with non-marking polyolefin tires and plate brakes. Overall height of caster assembly is 6" (15.2cm).

Optional Accessories and Modifications


F) Line-up interlock deviceST) Stainless steel trim strips

SW) Silverware cutouts with stainless steel bins

SW6 Six each silverware cutouts with stainless steel bins
 SW8 Eight each silverware cutouts with stainless steel bins
 SW10 Ten each silverware cutouts with stainless steel bins

UU) Molded fiberglass trim strips

V) 6" (15.2cm) high adjustable stainless steel legs in lieu of casters



Model KCTS-28


Custom shown with option SW, custom recessed body, custom slanted top.









Mobile Tray and Silver stands










PLAN VIEW KCTS-28

ELEVATION VIEW KCTS-28

END VIEW KCTS-28







PLAN VIEW KCTS-36

ELEVATION VIEW KCTS-36

END VIEW KCTS-36

Mechanical Data-Standard Unit

MODEL NUMBER	SHIP WEIGHT
KCTS-28	150 lbs/68 kg
KCTS-36	192 lbs/87kg