



Delta[®] 5-E

Project _____
 Item _____
 Quantity _____
 CSI Section 11400 _____
 Approval _____
 Date _____

Delta[®] 5-E

Models Delta[®] 5-E



Standard Features

- Functions as both a glass-washer and a dishwasher, accommodating wares up to 11-1/2" (292 mm) high
- Push-button start
- Electromechanical controls
- Easily accessible controls
- 3-way dispensing system for detergent, rinse additive and sanitizer
- Stainless steel wash pump
- Lower rotary wash arm and fixed upper jets
- Door safety switch
- Adjustable bullet feet
- Swing-out control box for easy service and access
- Side control panel for easy access to switches
- Dial temperature gauge for constant monitoring of temperature
- Side skirt panels
- Latch-type front (lower) panel
- Delime/manual wash switch

Options

- Water Hammer Arrestor
- Scale Prevention System (SPS)
- Replacement cartridge for SPS (2-pack)

Accessories

- 36-Compartment Rack
 - 4-1/8" tall (105 mm)
 - 5-5/8" tall (143 mm)
 - 7" tall (178 mm)
- Combination Rack
- Peg Rack
- Flat Rack
- Half Rack

Specifications

Uses only 1.16 gallons (4.39 liters) of water per cycle	11-1/2" (292 mm) wash chamber clearance
Cleans 40 racks per hour	Gravity drain
1,440 glasses per hour	Built-in waste accumulator
90-second operating cycle	Sustaining heating element maintains final rinse between 120°F (49°C) and 140°F (60°C)
Powerful 3/4 hp wash pump motor	Removable end plugs on lower wash arm and removable upper jets
Built-in chemical pumps	Durable 304 stainless steel construction
Air-gap water inlet	



Intertek





Delta® 5-E

SIDE VIEW

FRONT VIEW

OVERHEAD VIEW

A - Incoming Water Connection
 B - Drain Connection - 2" IPS
 C - Electrical Connection Point

NOTE: All vertical dimensions are at lowest point due to adjustable bullet feet and may be raised an additional 2 3/4".

MODEL NO.	MACHINE DIMENSIONS					SHIPPING INFORMATION					
	INSIDE CLEARANCE HEIGHT	INSIDE CLEARANCE WIDTH	INSIDE CLEARANCE DEPTH	DOOR OPEN DEPTH	WALL CLEARANCE	WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Delta® 5-E	11-1/2" (292 mm)	20-1/4" (514 mm)	20-1/2" (521 mm)	36-3/4" (933 mm)	2" (51 mm)	210 lbs (95 kg)	92.5	28.2 cu. ft.	51" (1295 mm)	29" (737 mm)	33" (838 mm)

APPROXIMATE TOTAL AMP LOADS		OPERATING CAPACITY	
115/60/1	16.0	Racks per Hour	40
		Dishes per Hour	1,000
		Glasses per Hour	1,440

WASH PUMP		OPERATING CYCLE	
Wash Pump	3/4 hp	Wash Cycle (seconds)	40
		Rinse Cycle (seconds)	24
		Dwell Time (seconds)	18
		Total Cycle (seconds)	85

BOOSTER HEATER		OPERATING TEMPERATURES	
Rinse Tank Booster Heater	2.0 kW	Wash (minimum)	120° F (48.9° C)
		Wash (recommended)	140° F (60° C)

WATER REQUIREMENTS		SANITIZERS AVAILABLE	
Gallons per Hour	46.4 gal (176 L)	Sodium Hypochlorite	50 PPM
Flow Rate (GPM)	6.33 gal (24 L)	Iodophor	12 PPM
Flow Pressure (PSI)	15 - 25		
Waterline Size (IPS)	1/2"		
Drainline Size (OD)	2"		
Tank Capacity	1.16 gal (4.39 L)		
Wash Pump Capacity (GPM)	61 gal (231 L)		

HOW TO SPECIFY: Delta® 5-E

Jackson WWS, Inc.
 Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734
 Mailing Address: P.O. Box 1060, Barbourville, KY 40906
 Telephone: 888-800-5672 • Fax: 606-523-1799
 Email: info@jacksonwws.com
 07610-004-13-56 [04/29/14]

www.jacksonwws.com

We reserve the right to change specifications in this bulletin without incurring any obligation for equipment previously or subsequently sold.