

TECHNICAL DATA SHEET FOR E33D5 ON THE SK33 STAND

Half Size Digital / Electric Convection Oven
on a Stainless Steel Stand

STANDARD FEATURES

- 5 half size sheet pan capacity
- 5 12" x 20" hotel pan capacity
- 3 $\frac{1}{3}$ " / 85mm tray spacing
- Compact 24" / 610mm width
- Digital display Time and Temperature Controls
- Large easy view $\frac{3}{4}$ " / 20mm high displays
- Electronic thermostat control
- Electronic timer with countdown or time count modes
- Programmable for up to 20 programs
- Moisture injection mode (5 levels)
- 2 speed bi-directional reversing fan system
- 5.8kW heating power
- Safe-Touch vented side hinged door
- Slam shut door latch
- Pendulum operation door handle
- Porcelain enameled oven chamber
- Plug-in continuous oven door seal
- Dual halogen oven lamps
- Anti-skid 2" / 50mm dia. 3" / 76mm high adjustable stainless steel feet
- 100% recyclable packaging

ACCESSORIES

- Optional M236060 Core Temperature Probe Kit
- Turbofan SK33 Oven Stand
- DSK33 Double Stacking Kit



E33D5

Unit shall be a Moffat electrically heated Turbofan convection oven E.T.L. listed and NSF-4 listed. The oven shall have a one piece porcelain enameled oven chamber, stainless exterior top and sides. The oven shall have a vented safe touch side hinged door with slam shut latching and pendulum operation door handle. Oven shall have capacity for 5 half size sheet pans or 5 12" x 20" steam pans. The oven shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven control shall allow both manual and programmed (20 programs) operating modes with programmable moisture level injection and 2 speed oven fan. A core temperature probe M236060 is optional. The oven shall include dual halogen oven lamps. The oven shall be able to be bench mounted on 3" feet or mounted on oven stand model SK33. Unit shall be supplied in 100% recyclable shipping packaging.

SK33

Unit shall be a Moffat Turbofan stainless steel oven stand NSF-4 listed. The stand shall be constructed from stainless steel tube with castors, with front castors having dual swivel and wheel locks. It shall be fitted with 5 tray runners suitable for up to 5 half size sheet pans or 5 12" x 20" steam pans. The stand shall be fully compatible with, and support, Turbofan Convection Oven models E33D5 and E33T5. Unit shall be supplied in 100% recyclable shipping packaging.

E33D5 Half Size Digital / Electric Convection Oven on a Stainless Steel Stand

CONSTRUCTION

Porcelain enameled fully welded oven chamber
 Stainless steel front, sides and top exterior
 Stainless steel oven fan baffle and oven vent
 Removable 5 position stainless steel side racks
 Stainless steel frame side hinged door
 0.2" / 5mm thick door outer glass
 0.2" / 5mm thick low energy loss door inner glass
 Stainless steel control panel
 Aluminised coated steel base and rear panels

CONTROLS

Electronic controls with Digital Time and Temperature display,
 Manual or Program modes
 Large ¾" / 20mm high LED displays
 Two individual time and temperature setting control knobs
 6 function keys
 ON/OFF key
 Fan LO speed key
 Timer Start / Stop key
 Moisture Injection key (5 moisture levels)
 Programs select key
 Actual temperature display key
 Adjustable buzzer / alarm volume
 Thermostat range 120-500°F
 Timer range from 180 minutes in countdown mode
 Timer range up to 999 minutes in time count mode for holding, slow cooking
 Over-temperature safety cut-out
 Optional core temperature probe

CLEANING

Stainless steel top and side exterior panels
 Porcelain enameled oven chamber
 Fully removable stainless steel oven side racks
 Removable stainless steel oven fan baffle
 Easy clean door system with hinge out door inner glass (no tools required)
 Removable plug-in oven door seal (no tools required)
 3" / 76mm high stainless steel feet for easy access underside

SPECIFICATIONS

Electrical Requirements
 208V, 60Hz, 1P+N+E, 5.8kW, 27.8A
 220-240V, 60Hz, 1P+N+E, 6.0kW, 25A
 No cordset supplied

Water Requirements (optional)

Cold water connection ¾" GHT male
 80psi maximum inlet pressure / 20psi minimum inlet pressure

External Dimensions

Width 24" / 610mm
 Height 28¾" / 730mm including 3" / 76mm feet
 Depth 26¾" / 680mm

Oven Internal Dimensions

Width 13" / 330mm
 Height 20¼" / 515mm
 Depth 22½" / 570mm
 Volume 3.53ft³ / 0.10m³

Oven Rack Dimensions

Width 13" / 330mm
 Depth 20⅞" / 530mm

Nett Weight (E33D5)

158lbs / 71.5kg

Packing Data (E33D5)

205lbs / 93kg
 Width 25¾" / 655mm
 Height 31¾" / 805mm
 Depth 32¾" / 830mm
 Volume 15.5ft³ / 0.44m³

SK33 Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan E33D and E33T Series ovens
 5 position tray runners standard
 Welded 1½" / 38mm and 1¼" / 32mm square tube front and rear frames
 Welded rack supports/side frames
 3" / 76mm diameter swivel castors standard with 2 front castors wheel and swivel lock
 Supplied CKD for assembly on site

External Dimensions (SK33 Oven Stand)

Width 24" / 610mm
 Height 34⅝" / 880mm
 Depth 25⅝" / 650mm

Nett Weight (SK33 Oven Stand)

40lbs / 18kg

Packing Data (SK33 Oven Stand)

45lbs / 20.5kg
 3.53ft³ / 0.10m³
 Width 29¾" / 755mm
 Height 31¼" / 795mm
 Depth 6¼" / 160mm

INSTALLATION CLEARANCES

Rear 2" / 50mm
 LH Side 2" / 50mm
 RH Side* 3" / 75mm
 * For fixed installations a minimum of 20" / 500mm is required for service

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 12" / 300mm from the appliance sides is required



www.moffat.com

U.S.A.

Moffat Inc
 3765 Champion Boulevard
 Winston-Salem
 North Carolina 27105
 Ph Toll Free 1-800-551 8795
 Ph 336-661 0257
 Fax 336-661 9546
 Email sales@moffat.com
 www.moffat.com

Manufactured by:

Moffat Limited
 16 Osborne Street PO Box 10-001
 Christchurch 8081 New Zealand



ISO9001
 Quality Management Standard

Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
 Moffat 1297 / 1.13

