

## Heavy Duty - Automatic Electric Griddles



### Industry Leading Features

- ✔ Controlled Zone Heating - 1 heating element and 1 temperature controller for each 12" of griddle surfaces.
- ✔ Heavy duty tubular incoloy metal sheath element pressure clamped to griddle plate for more uniform temperature distribution.
- ✔ Fast Preheat - 350 degrees in 7-8 minutes.
- ✔ Precision thermostat with pilot light indicator.
- ✔ Front mounted electrical access panel for ease of service.
- ✔ Stainless steel splash guards and grease trough welded to griddle unibody construction.
- ✔ 5/8" thick griddle plate, machine polished for fast heat-up and quick recovery.
- ✔ 7 quart all stainless steel drawer with baffle.
- ✔ MEA #490-84E

Model #	Griddle Area	Overall Width	Overall Depth	240V/Amp	208V/Amp	Elements Required	Ship Weight
EL1812*	18" x 12"	12"	21"	4KW/17	3KW/15	1	81 lbs.
EL1824**	18" x 24"	24"	22½"	8KW/34	6KW/29	2	150 lbs.
EL1836**	18" x 36"	36"	22½"	12KW/50	9KW/44	3	225 lbs.
EL1848**	18" x 48"	48"	22½"	16KW/67	12KW/58	4	300 lbs.

Plate Thickness: ⅝" Working Height: 13 ⅝" \*Single phase only, also available in 120 Volt, specify voltage, line cord included  
 \*\* Specify single phase or 3 phase

