Item#

# F-2001MRH-C

MODULAR CUBELET ICE MACHINE


Project:


# \*AutoCad available on KCL

F-2001MRH-C 7/14 Item #13342

# **CUBELET DIMENSIONS**

# F-2001MRH-C $30 \times 27^{1/2} \times 34^{7/16}$





# F-200 I MRH-C

Remote Air-Cooled Shown on an optional B-900




Also available on Large Bins: B-1150SS B-1300SS B-1500SS

- Up to 1814 lbs. of ice production per 24 hours
- Durable stainless steel exterior
- Advanced CleanCycle24<sup>®</sup> Design



- Removes sediment
- Cleaner ice
- Longer life and easy maintenance
- R-404A Refrigerant

# \*CUBELET DIMENSIONS



\*approximate size in inches, image not to scale





# **Warranty**

Valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in

Three Year - Parts & Labor on entire machine. (Serial numbers Vxxxxx) and after.) Five Year - Parts on: Compressor, air-cooled condenser.

# © HOSHIZAKI AMERICA, INC.



# DIMENSIONS W x D x H F-2001MRH-C 30 x 27<sup>1/2</sup> x 34<sup>7/16</sup>

# F-2001MRH-C MODULAR CUBELET ICE MACHINE

Remote Air-cooled

# **REMOTE AIR-COOLED**

Water Temp° F.		50°	70°	90°
ĵ F.	70°	1814	1749	1700
Temp°	80°	1652	1605	1559
Αġ	90°	1515	1496	1430

# **UTILITY CONSUMPTION**


Model Number	KWH per 100 LBS. 90/70	Potable Water Gal. per 100 lbs.
F-2001MRH-C	5.1	12.0


# **SPECIFICATIONS**

Model Number	Amperage	Min. Circuit Ampacity	Shipping Weight
F-2001MRH-C	19.94	30	360 lbs.

# **STORAGE BINS**


Model Number	Application Capacity	ARI-Rated Capacity	
B-500	500 lbs.	360 lbs.	
B-700	700 lbs.	550 lbs.	
B-800	800 lbs.	600 lbs.	
B-900	900 lbs.	660 lbs.	
B-1150	1150 lbs.	N/A	
B-1300	1275 lbs.	N/A	
B-1500	1490 lbs.	N/A	
B-1650	1605 lbs.	N/A	






FRONT VIEW







RIGHT SIDE VIEW



# REMOTE AIR-COOLED UNIT



ICE DROP ZONE



Voltage supply for the URC Remote Condenser is supplied from the Ice Maker. No additional circuit is required.

Pre-Charged Tubing Kits (Sold Separately) 20' R404-20610 35' R404-35610 55' R404-55610

# **ELECTRICAL & PLUMBING/F-2001MRH-C**

- 208-230/60/1 (3 wire dedicated neutral for 115V)
- 3/8" OD copper or equivalent independent water supply with 1/4" nominal ID minimum
- 3/4" FPT independent drain connection

# (NSE) CUL) US LISTED (SO) 150 14001 © HOSHIZAKI AMERICA, INC.

# **OPERATING LIMITS**

- Ambient Temp Range
- Water Temp Range
- Water Pressure
- Voltage Range

# SERVICE

- Panels easily removed and all components accessible for service.
- · Removable/cleanable air filter.



45 - 100°F

10 - 113psig

187 - 253V

45 - 90°F