

Reach In Dual Temps



SKT-22/22-FA

Height w/casters 82.5"
 Length 56.63"
 Depth 34.5"



SKT-48/22-FA

Height w/casters 82.5"
 Length 84.63"
 Depth 34.5"

Features

- Stainless steel doors & exterior sides
- Heavy duty hinge with self closing mechanism
- Stainless steel floor aluminum interior
- Recessed handle with cylinder lock
- Heavy duty epoxy coated shelves
- Robust body with 2-1/2" thick walls, injected with CFC-free polyurethane
- Control panel with temperature display, door ajar light, power indicator condensing switch
- 5" casters
- Door locks
- NSF 7
- Forced air evaporator for rapid temperature "Pull Down"
- 2 Self contained heavy duty condensing units and 404A (freezer) & 134a (refrigerant)
- 10' power cord

Model No.	Description	Voltage	Amps	Temp	HP	Est. Ship Weight
SKT-22/22-FA	R: 1 Door/3 Shelves	115	6.6	32°F - 39°F	1/3	520#
	F: 1 Door/3 Shelves	115	10	0°F - 10°F	1/3	
SKT-48/22-FA	R: 2 Door/6 Shelves	115	10	32°F - 39°F	1/2	630#
	F: 1 Door/3 Shelves	115	10	0°F - 10°F	1/3	



Technical Data / Reach In Dual Temps



Model #	SKT-22/22-FA		SKT-48/22-FA	
Outside Dimensions				
Depth w/drain	34.5"		34.5"	
Length	56.63"		84.63"	
Height w/casters	82.5"		82.5"	
Door Size	25.75" x 60.75"		25.75" x 60.75"	
Door Type	2 swing		3 swing	
Inside Dimensions				
Depth	29.5"		29.5"	
Length	22.75"/22.75"		52"/22.75"	
Height	58"		58"	
Shelf Size	21.75" x 27"		21.75" x 27"	
# of Shelves	8		12	
Capacity: Cubic Foot	22.75/22.75		50/22.75	
Specifications				
	Refrigerator		Freezer	
Operating Temperature	32°F to 39°F		0°F to 10°F	
Refrigerant	134a		404A	
Compressor Size HP	1/3		1/2	
Defrost			3@30min	
Voltage	115		115	
Amperage	6.6		10	
Cord and Plug	yes		yes	
Shipping Dimensions				
Depth	40"		40"	
Length	61"		92"	
Height	88"		88"	
Gross Weight lbs.	520		630	
Cubic feet	124		187	

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

