

Reach In Refrigerators - Top Mount - Narrow



SAV-20-T

Height w/casters 78.5"
 Length 23"
 Depth 31.5"



SAV-40-T

Height w/casters 78.5"
 Length 46.75"
 Depth 31.5"

Features

- Stainless steel doors
- Heavy duty hinge with self closing mechanism
- Aluminum interior
- Recessed handle
- Heavy duty epoxy coated shelves
- Robust body with 2-1/2" thick walls, injected with CFC-free polyurethane
- External temperature display and power indicator
- 5" casters
- Door locks
- NSF 7
- Self contained heavy duty 134a condensing unit
- Forced air evaporator for rapid temperature "Pull Down"
- 10' power cord

Model No.	Description	Voltage	Amps	Temp	HP	Est. Ship Weight
SAV-20-T	1 Door/3 Shelves	115	7	32°F - 39°F	1/4	252#
SAV-40-T	2 Doors/6 Shelves	115	9	32°F - 39°F	1/3	366#

Technical Data / Reach In Refrigerators



Model #	SAV-20-T	SAV-40-T
Outside Dimensions		
Depth with Drain	31.5"	31.5"
Length	23"	46.75"
Height with Casters	78.5"	78.5"
Door Size	20.25" x 56.75"	20.25" x 56.75"
Door Type	1 swing	2 swing
Inside Dimensions		
Depth	27.38"	27.38"
Length	18.25"	42"
Height	54.63"	54.63"
Shelf Size	17.75" x 25.75"	20.25" x 23.625"
# of Shelves	3	6
Capacity: Cubic Foot	20	40
Specifications		
Operating Temperature	32°F-39°F	32°F-39°F
Refrigerant	134a	134a
Compressor Size HP	1/4	1/3
Voltage	115	115
Amperage	7	9
Cord and Plug	yes	yes
Shipping Dimensions		
Depth	35"	35"
Length	30"	52"
Height	85"	85"
Gross Weight lbs.	252	366
Cubic feet	51	89

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

