

2 and 3 Glass Door Merchandisers



VR-35-RE-US

Height 74"
 Length 56"
 Depth 25.75"
 Cubic Ft. 35
 Liters 991
 Bottles (20 oz) 404
 Cans (12oz) 904



CR-49-US

Height 78"
 Length 60"
 Depth 29.5"
 Cubic Ft. 49
 Liters 1,388
 Bottles (20 oz) 620
 Cans (12oz) 1,422



CR-65-US

Height 78"
 Length 78"
 Depth 29.5"
 Cubic Ft. 65
 Liters 1,842
 Bottles (20 oz) 830
 Cans (12oz) 1,926

Features

- Interior and exterior constructed of heavy duty white coated steel
- Stainless steel floor
- Polyurethane insulation with cyclopentane as blowing agent
- Double pane glass door with Low-E protection
- Illuminated top header sign
- Externally mounted hinged glass doors
- Recessed door handle
- Heavy duty shelves with clips
- Heavy duty hinges with self closing mechanism
- Forced air evaporator for rapid temperature "Pull Down"
- Self contained heavy duty 134a condensing unit
- Energy efficient LED lighting
- UL Classified to ANSI/NSF 7

Model No.	Description	Voltage	Amps	Temp	HP	Est. Ship Weight
VR-35-RE-US	2 Door/6 Shelves	115	8.4	32°F - 39°F	1/3	515#
CR-49-US	2 Door/8 Shelves	115	10.8	32°F - 39°F	1/2	698#
CR-65-US	3 Door/ 12 Shelves	115	16	32°F - 39°F	3/4	810#



Technical Data / 2 and 3 Glass Doors



Model #	VR-35-RE-US	CR-49-US	CR-65-US
Outside Dimensions			
Depth	25.75"	29.5"	29.5"
Length	56"	60"	78"
Height	74"	78"	78"
Door Size	28"x47.75"	30"x55.75"	25.75"x55.75"
Door Type	2 swing	2 swing	3 swing
Inside Dimensions			
Depth	21.75"	25.25"	25.25"
Length	51.25"	55.25"	73.25"
Height	54.75"	61.25"	61.25"
Shelf Size	(3) 24.5"x17.875" (3) 26.125"x17.875"	(8) 27.13"x21.625"	(8) 22.13"x22.375" (4) 27.75"x22.375"
# of Shelves	6	8	12
Capacity: Cubic Foot	35	49	65
Specifications			
Operating Temperature	32°F-39°F	32°F-39°F	32°F-39°F
Refrigerant	134a	134a	134a
Compressor Size HP	1/3	1/2	3/4
Voltage	115	115	115
Amperage	8.4	10.8	16.0
Cord and Plug	yes	yes	yes
Shipping Dimensions			
Depth	30"	34"	34"
Length	60"	64"	82"
Height	80"	84"	84"
Gross Weight lbs.	515	698	810
Cubic feet	83	106	135

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

VR-35-RE-US

