R-290 Glass Door Merchandiser



DECK-12-HC

 Height
 62"

 Length
 25.63"

 Depth
 22.75"

 Cubic Ft.
 12

 Liters
 340

 Bottles (20 oz)
 168

 Cans (12oz)
 384





R 290 HYDROCARBON REFRIGERANT GAS

The innovative HC model uses hydrocarbon R-290 as the refrigerant, which has no global warming potential (GWP) and is the first of its kind in the world with UL and NSF approval, in compliance with all safety and sanitation norms.

Moreover, the HC model is an ENERGY STAR® qualified refrigerator thanks to its low energy consumption.

FOGEL once again shows its commitment to sustainability by innovating with environmentally friendly refrigerators while increasing product value.

* R-290 (propane grade refrigerant)

Features

- Hydrocarbon R-290 refrigerant, which is environmentally friendly and makes the HC-12 a greener cooler
- ENERGY STAR® (Deck-12-HC) qualified model due to it's high energy efficiency
- Electronic control with energy saving button and three different temperature range settings
- Double pane glass door with Low-E protection to avoid condensation.
- 4 Heavy duty adjustable shelves
- Robust body made of pre-painted galvanized steel
- 1/4 HP heavy duty condensing unit for R-290, with easy access for service
- Polyurethane insulation with cyclopenthane as blowing agent
- Energy efficient LED lighting


| Model No. | Description | Voltage | Amps | Тетр | HP | Est. Ship Weight |
|--------------|------------------|---------|------|-------------|-----|---------------------|
| DECK-10-HC | 1 Door/3 Shelves | 115 | 3.3 | 32°F - 39°F | 1/4 | 225# |
| DECK-12-HC | 1 Door/3 Shelves | 115 | 4.2 | 32°F - 39°F | 1/4 | 255# |
| DECK-19-HC | 1 Door/4 Shelves | 115 | 6.0 | 32°F - 39°F | 1/3 | 518# |




Technical Data / R-290 Glass Door Merchandiser



| Model # | DECK-10-HC | DECK-12-HC | DECK-19-HC | |
|-----------------------|---------------|---------------|--------------|--|
| Outside Dimensions | | | | |
| Depth | 22.75" | 22.75" | 25.75" | |
| Length | 25.63" | 25.63" | 28.25" | |
| Height | 54" | 62" | 79" | |
| Door Size | 25.25"x39.19" | 25.25"x47.19" | 28"x64.69" | |
| Door Type | 1 swing | 1 swing | 1 swing | |
| Inside Dimensions | | | | |
| Depth | 19" | 19" | 22" | |
| Length | 22" | 22" | 24.75" | |
| Height | 36.5" | 44.5" | 62" | |
| Shelf Size | 21.75"x17.5" | 21.75"x17.5" | 21.75"x17.5" | |
| # of Shelves | 3 | 4 | 5" | |
| Capacity: Cubic Foot | 10 | 12 | 19 | |
| Specifications | | | | |
| Operating Temperature | 32°F-39°F | 32°F-39°F | 32°F-39°F | |
| Refrigerant | 134a | 134a | 134a | |
| Compressor Size HP | 1/4 | 1/4 | 1/3 | |
| Voltage | 115 | 115 | 115 | |
| Amperage | 3.3 | 4.2 | 6 | |
| Cord and Plug | yes | yes | yes | |
| Shipping Dimensions | | | | |
| Depth | 27" | 27" | 30" | |
| Length | 30" | 30" | 34" | |
| Height | 62" | 69" | 85" | |
| Gross Weight lbs. | 225 | 255 | 518 | |
| Cubic feet | 29 | 32 | 50 | |





- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

