

www.falconequipment.com

879 South 4400 West Salt Lake City, UT 84104

Phone: 888.987.7894



- Foamed-in-place polyurethane insulation
- Bottom mount condensing unit
- Removable door gasket for easy cleaning
- Automatic defrosting
- Stainless steel floor
- Copper evaporator
- Black powder-coated steel exterior
- Eco-friendly R290 hydrocarbon refrigerant
- 5" Casters
- ETL listed. Conforms to UL STD. 471, Certified to CSA STD. C22. 2No.120

Standard Features - Glass Door Freezer Model #AGM-26F

Conforms to NSF/ANSI STD. 7.

Model #AGM-26F

Coolina

Temperature Range -5°F-2°F Refrigerant R290 Max. Ambient Temperature 90°F **Defrosting Automatic** Temperature Controller Digital Horsepower 3/4

Electrical

Voltage 115 Amps 9.4 Hz 60 Phase

Plug Type NEMA-5-15P

Electrical Cord Length

Construction

Exterior Material **Powder Coated**

Cold Rolled Steel

Interior Material Painted Aluminum Door Type Glass Swing Doors

Insulation Material Foamed-In-Place Polyurethane Shelf Size

(4) 24-1/4" x 23-1/4" **Epoxy-Coated Steel**

Shelf Load Capacity 90 lbs.

Shelf Material

Dimensions

Exterior Dimensions 26"W x 26.5"D x 54.5"H Interior Dimensions 21.50"W x 21.5"D x 33.5"H Shipping Dimensions 29.5"W x 30"D x 63"H

> Net Volume 23 cu. ft. Net Weight 408 lbs. Gross Weight 488 lbs.











PLAN VIEW

Front View



Side View



Top View

