





Customer/Wholesaler:	Date:	Job Name:	Model Specified:	Quantity:
Contractor:		Architect/Engineer:		



MODEL	DESCRIPTION	DIM A	DIM B	DIM C
82220	PRERINSE SLP SWCDLH 06SS NP EL	6" [152mm]	7 7/16" [188mm]	11 1/8" [282mm]
70120	PRERINSE SLP SWCDLH 12SS NP EL	12" [305mm]	9" [229mm]	12 11/16" [323mm]




PRODUCT SPECIFICATIONS: SINGLE WALL LOW PROFILE SPRING PRERINSE UNIT 1.15 GPM @ 60 PSI, WITH CERAMIC CARTRIDGE, LEVER HANDLE, ADDON FAUCET, SWING SPOUT 12.5 GPM @ 60 PSI, CLOSE NIPPLE, CLOSE ELBOW

PRODUCT COMPLIANCE:
ASME A112.18.1 / CSA B125.1
NSF 61 - Section 9
NSF 372 (Low Lead Content)
2019 DOE PRSV - Class II

Customer/Wholesaler:	Date:	Job Name:	Model Specified:	Quantity:
Contractor:	Architect/Engineer:			

REPLACEMENT PARTS



PRODUCT SPECIFICATIONS: SINGLE WALL LOW PROFILE SPRING PRERINSE UNIT 1.15 GPM @ 60 PSI, WITH CERAMIC CARTRIDGE, LEVER HANDLE, ADDON FAUCET, SWING SPOUT 12.5 GPM @ 60 PSI, CLOSE NIPPLE, CLOSE ELBOW

PRODUCT COMPLIANCE:
ASME A112.18.1 / CSA B125.1
NSF 61 - Section 9
NSF 372 (Low Lead Content)
2019 DOE PRSV - Class II