U.S. Range

Heavy-Duty Gas CSI Section 11400 Approved ___ Ceramic Briquette Date Charbroiler w/Adjustable Grates

Models

- UTBG24-AB24
- UTBG48-AB48
- UTBG36-AB36
- UTBG60-AB60



Model UTBG24-AB24

Standard Features

- · Stainless steel front, sides and back
- 4" stainless steel adjustable legs
- 3/4" NPT gas regulator with "T" gas manifold connection for straight through rear or flush-mount gas connections.
- Stainless steel front rail; 4" (102mm) deep overall with 3 1/2" (89mm) top work surface
- Stainless steel large capacity crumb
- Reversible cast-iron broiler racks in 3" wide sections with 1/8" and 3/16" brand marks.
- 21-3/16" (538mm) broiling grid depth
- 2-position adjustable broiler grate
- One cast-iron 30,000 BTU burner for every 12" of broiler width.
- · One variable on/off valve control for each burner.
- Ceramic, pre-formed briquettes

Options & Accessories

Item Quantity

- Stainless steel skirt for dais/counter surface mounting. The stainless steel skirt will reduce overall unit height by 1 3/4" (44.45mm).
- · Stainless steel spatter-guard
- · Removable wire holding shelf for spatter guards available for 24" and 36" models
- Broiler grate cleaning tool
- Fajita broiling grate: 9" wide, replaces 3 standard grate sections on the left or right end of the broiler. Limit one per broiler.
- Stainless stand with solid top holding shelves, and adjustable feet or with casters
- Set of revisible cast iron broiler racks with four brand marks per 3" section. Brand 3/16" wide.
- Removable stainless steel attachment condiment rail with universal 1/9 or 1/3 food pan cut outs (pans supplied by others)

Specifications

US Range gas ceramic briquette broilers are available with adjustable broiling grates, in four nominal imperial widths from 24"(600mm) to 60"(1500mm). 13" (330mm) high and 32" (814mm) deep.

Reversible cast-iron grates in 3" (76mm) wide sections overall cooking area depth 21 3/16" (538 mm).

One 30,000 BTU burner with individual valve control per 12" of broiler width.

Large stainless steel catch tray, stainless steel front, sides, and back.










U.S. Range





For use with Natural or Propane gas only. Gas input ratings shown for installations up to 2000 ft., (610m), above sea level. Please specify altitudes over 2000 ft. and gas type when ordering.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only.

Garland/U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

* PLEASE ADD 7" [178mm] IN OVERALL DEPTH WITH ATTACHMENT CONDIMENT RAIL OPTION





Model #	Width In (mm)	Height (w/std legs)	Depth In (mm)	Total Input (BTU)	Shipping Information	
					Lbs/Kg	Cu Ft
UTBG24-AB24	23-5/8 (600)	13 (330)	32 (814)	60,000	283/129	19
UTBG36-AB36	35-7/16 (900)			90,000	391/178	26
UTBG48-AB48	47-1/4 (1200)			120,000	514/283	34
UTBG60-AB60	59-1/16 (1500)			150,000	635/288	41

Supply Operating Pressure			Manifold Operating Pressure				Installation Clearances		
Natural Gas Propane		Propane	Natural Gas		5	Propane		Clearance: 0" For Installation	
"WC	MBar	"WC	Mbar	"WC	MBar	"WC	Mbar	In Non-Combustible Surroundings Only	
7	17.5	11	27.5	4.5	11	10	24.5		

Garland reserves the right to make changes to the design or specifications without prior notice.

