



www.glastender.com




Dimensional Information









To view cleaning and care instructions, please visit: https://www.glastender.com/PDF/F-423-011_ss_clean_care.pdf

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.

Project:		AIA#
Item #:	Qty:	SIS#
Model #:	· · · · · · · · · · · · · · · · · · ·	510

Drop-In Rinser Faucet

DI-RF7, DI-RF12, DI-RF18, DI-RF24

Standard Features

- All stainless steel construction
- · Pan includes radius interior corners for easy cleaning
- Drain is a 1/2" welded tailpiece that exits from the bottom of the unit
- Drain pan includes 1/2" flange
- Installation kit includes: 10' of clear vinyl drain tube, five 4" Ty-wraps, and two 1/2" plastic elbows
- Install by making cut-out in work surface (see Cut-Out Dimensions under Specifications). Apply silicone sealant to underside of flange. Set in place and finish plumbing the unit.

Installation Notes

- Important: Unit must be installed in conformance with applicable federal, state, and local plumbing codes, including adequate backflow when required.
- Must install backflow prevention device conforming to ANSI/ASSE 1022 or ANSI/ASSE 1024 to meet plumbing code (not included).
- Install in-line water regulator (included).
- A separate shut-off valve is recommended (not included).

Specificatons

Drains

• 1/2" welded tailpiece

Cut-out Dimensions

- Model DI-RF7 6-1/4" by 6-1/4"
- Model DI-RF12 6-1/4" by 11-1/4"
- Model DI-RF18 6-1/4" by 17-1/4"
- Model DI-RF24 6-1/4" by 23-1/4"

Materials

All stainless steel

- Faucet
 - Accepts 3/8" cold water lead
 - 30 psi water pressure regulator included
 - 1.2 gallons per minute



Approval/Notes:

ns please visit our website.