

AURA 3 groups



Ref602949 (UAURA3UL)

Traditional espresso maker, 3 Maestro groups, 15,6 liter boiler, 3 control boxes with 4 programmable dosing program, Steamglide lever, programmable water & steam

General Features

The professional semi-automatic AURA line owns all the technical features of a high-end traditional espresso machine, offering the perfect harmony of aesthetics and performance. With its modern design of stainless steel and chrome, the AURA displays an assertive silhouette underlined with LED lighting of the tray grill and around the electronic control boxes with touchscreen interface for an intuitive programming. AURA is dedicated to users familiar with volumetric commands that address high performance and consistency in the extraction process. The MAESTRO thermo-regulated brew groups are fitted with the EASYLOCK system that help locking and sealing the portafilter with minimal effort. The AURA line offers a set of advanced technologies that warrant an outstanding coffee extraction quality and a strong hot water/steam power.

AURA 3 groups

Main Features

- Programmable water and steam.
- Automatic cleaning cycle.
- The professional semi-automatic AURA line owns all the technical features of a high-end traditional espresso machine, offering the perfect harmony of aesthetics and performance.
- Modern design of stainless steel and chrome, the AURA displays an assertive silhouette underlined with LED lighting of the tray grill and around the electronic control boxes with touchscreen interface for an intuitive programming.
- AURA is dedicated to users familiar with volumetric commands that address high performance and consistency in the extraction process.
- The MAESTRO thermo-regulated brew groups are fitted with the EASYLOCK system that help locking and sealing the portafilter with minimal effort.
- Electronic pre infusion.
- Double paneled cup warmer with large capacity.
- USB interface for update.
- 3 Maestro groups.
- 3 independent control boxes with 4 programmable dosing selection, start/stop, shot time display.
- Manual Steamglide lever.

Construction

- Stainless steel body.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.
- Easylock portafilter.
- RS-232 protocol for computer/cashier interface.
- 15.6 liter boiler.

Included Accessories

- 1 of - NOT TRANSLATED - PNC 871008
- 3 of - NOT TRANSLATED - PNC 871009

AURA 3 groups

Electric

Supply voltage:

602949 (UAURA3UL) 220 V/1N ph/60 Hz

Electrical power, max: 4.3 kW

Plug type:

Water:

Cold water temperature

(min/max): 5 / 60 °C

Key Information:

External dimensions,

Width: 38 3/4" (984 mm)

External dimensions,

Depth: 23 5/16" (592 mm)

External dimensions,

Height: 19 5/16" (490 mm)

External dimensions,

Weight: 183 lbs (83 kg)

Net weight: 183 lbs (83 kg)

Shipping width: (1320 mm)

Shipping depth: (750 mm)

Shipping height: (840 mm)

Shipping weight: lbs (103 kg)

Shipping volume: 0.8 m³

Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.02.09

Part of



Electrolux
Professional
Group

UNIC