

# Heated Holding Cabinets

### HHC-900 SimpleHold Full-size

Heated Holding Cabinets keep foods hot and tasty for long periods of time before serving. The right holding cabinet can make the difference between what you sell and what you throw away.





Full size, high volume, mobile heated holding cabinet with dual doors and single control panel. Designed to hold foods within proper temperature ranges prior to serving. Utilizes lower-wattage heaters than "standard" HHC-900 heated holding cabinet.

#### Configuration

The HHC-900 SimpleHold is only available in the following configuration:

- Solid back cabinet.
- Stainless steel doors with right side hinges.

#### **Main Features**

- Simple**Hold** control features simple to use electronic touch pad control with LED display for temperature setpoint changes.
- Lower wattage heaters (1500W) enable unit to be sold in both the USA and Canada.
- Removable air ducts for easy cleaning.
- Dual heavy-duty blower motors.
- Ventilated side racks.
- Large stainless steel water pan.





- Partial pan removal for convenient loading and unloading.
- Fully insulated doors, sidewalls and control module.
- Full perimeter door gasket.
- Self-closing, lift-off doors stay open past 90 degrees.
- Magnetic door latch and heavy-duty plated hinges.
- Standard 5 in. (127 mm) casters, two locking.



HHC-900 with SimpleHold controls and right-hand hinged doors..

Henny Penny Corporation PO Box 60 Eaton OH 45320 USA

+1 937 456.8400

+1 937 456.8434 Fax

**Toll free in USA** 800 417.8417 800 417.8434 Fax

www.hennypenny.com



71 ¼ in. (1810 mm)

## HHC-900 SimpleHold Specifications

#### **Dimensions**

Clearances

Capacity

Electrical

NA

HHC-900 with SimpleHold controls - Full-size

13 sheet pans 18 x 26 in (457 x 660 mm)

on 3 ¾ in (95 mm) centers.

24 ¾ in. (628 mm)

Heating160-210°F (71-99°C)WaterOne gallon water pan

Shipping Weight 372 lbs. (169 kg)

**Shipping Cube Dimensions** L x W x H  $74\frac{3}{4}$  x  $35\frac{1}{2}$  x 31 in (190 x 90 x 79 cm)

Listings UL, UL Sanitation, CUL, CE



Simple <b>Hold</b> controls					
Voltage	Phase	Cycle/Hz	Watts	Amps	Wire
120	1	50 or 60	1676	13.97	2+G

Power cord and plug included with USA and Canada destinations, only:

USA/Canada 120V plug type: Straight (standard) 5-20P plug. NEMA 5-20F

31 ¾ in. (806 mm)

Specifications subject to change without notice. For up-to-date product information, please visit www.hennypenny.com.

Order from:

Manufactured by:

Henny Penny Corporation PO Box 60 Eaton OH 45320 USA