








- Top glass angles down
- Ceiling easier to clean
- NSF approved thermometer
- 80 Degrees F maximum ambient
- Large diameter 1 inch drains at front
- Load line is 3.5 inches above the floor
- Larger front to back interior, 11 inches
- Interior floor has a radius at all four sides
- Self-contained refrigeration unit -easy to install
- Condenser airflow is in the back and out the side
- Large diameter upper evaporator with tin plating
- Solid food plates with radius groove to fit sushi foods
- Larger condenser face area improves cooling performance
- Slightly taller doors with plastic seal at end, opposite of the handle
- Food plates can be turned upside down and used to improve cooling performance



© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA30269

TEL1-800-438-6087

FAX 1-800-345-1325



HNC-120AA

Right or Left Handed HNC-150AA

Right or Left Handed HNC-180AA

Right or Left Handed

HNC-210AA Right or Left Handed



www.hoshizaki.com

COUNTER TOP REFRIGERATED DISPLAY CASE

HNC-120A (RIGHT OR LEFT HANDED) HNC-150A (RIGHT OR LEFT HANDED)

HNC-180A (RIGHT OR LEFT HANDED)

HNC-210A (RIGHT OR LEFT HANDED)



■ Larger condenser face area improves cooling performance




	R-134A REFRIGERANT	S E R V I C E Removable/cleanable air filters.
ONEYEAR - Parts & Labor on entire unit.		Removable/cleanable all filters.
TWOYEAR -Parts & Labor on compressor, Evaporator, Air-Cooled Condenser		
FIVEYEAR - Parts on: Compressor; Air-Cooled Condenser		

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact Factory for Warranty in other Countries.

OPERATING LIMITS Ambient Temp Range 50 - 86°F Voltage Range 104 - 126V Saturation Temp. (80°F Ambient Temperature)

ELECTRICAL 115/60/1

HOSHIZAKI COUNTER SHOW CASE					
Model	HNC-120AA-L(R)	HNC-150AA-L(R)	HNC-180AA-L(R)	HNC-210AA-L(R)	
AC Supply Voltage Power Supply Capacity Rated Amperage Starting Amperage Electric Consumption	1 Phase 115V 60Hz 0.47kVA (4.7A) 3.0A 13A 195W				
Saturation Temperature	Approx. 39°F (Ambient Temp. 80°F, No Load)				
Net Capacity	1.48 ft ³	2.01 ft ³	2.54 ft ³	3.07 ft ³	
Ambient Temperature	50 - 80°F				
Voltage Variation	Rated Voltage ±10%				
Exterior Dimensions (W) (D) (H)	47 1/4 inches 13 1/2 inches 11 inches	59 inches	71 inches	823/4 inches	
Interior Dimensions (W) (D) (H)	33 1/4 inches 11 1/4 inches _(bottom) 6 1/8 inches	45 inches	563/4 inches	683/4 inches	
Exterior	Glass, ABS Plastic,PVC Plastic,Galvanized Steel				
Interior	Glass, ABS Plastic, Stainless Steel				
Insulation	Polyurethane Foam				
Refrigeration System	Convection Cooling				
Sliding Door	2 pieces	4 pieces			
Net Weight/ Shipping Weight	66 lb. / 82 lb.	79 lb. / 99 lb.	92 lb. / 117 lb.	106 lb. / 134 lb.	
Shipping Dimensions (W) (D) (H)	50 1/2 inches 16 1/4 inches 16 inches	621/4 inches	74 inches	86 inches	
Accessories - Food Mount Plug Vinyl Hose Joint	3 pieces 4 pieces 1 piece 2 pieces	4 pieces	5 pieces	6 pieces	





HNC-120AA-L



HNC-120AA-R



HNC-150AA-R(L)



HNC-180AA-R(L)



Service cabinet, not for overnight storage

HNC-210AA-L(R)

We reserve the right to change specifications without notice.