



# **Indigo™ Series** 500 Ice Cube Machine

□ID-0502A □IY-0504A □IR-0501W □ID-0503W □IY-0505W IR-0500A Model: ID-0592N \*

> Indigo Series i-500 Ice Machine on B-570 Bin

### **Specifications**

#### **BTU Per Hour:**

6,100 (average) 6,900 (peak)

#### Refrigerant:

R-404A CFC-free

#### **Operating Limits:**

- · Ambient Temperature 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA)

Max. 80 psi (551.1 kPA)

#### Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 available in Air and Water-Cooled models only)

#### Minimum circuit ampacity:

Air cooled: 14.2 Water Cooled: 13.5 Remote: 20.0

#### Maximum fuse size:

Air Cooled: 20.0 Water Cooled: 20.0 Remote: 25.0

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- Space-Saving Design Up to 560 lbs. (254 kgs.) daily ice production and only 30" (76.20 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **DuraTech™ Exterior** provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce<sup>™</sup> Growth Inhibitor controls the growth of bacteria and yeast within the foodzone.



# Ice Shape



**Half Dice** 3/8" x 11/8" x 7/8" (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)



Regular 11/8" x 11/8" x 7/8" (2.86 x 2.86 x 2.22 cm)













2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







## i-500 on B-570 24.50" (62.23 cm) Storage Bin (2) Options B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) () 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units) () 1/2" (1.27 cm) Auxillary Base Drain Socket A © 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain (G) 3/4" (1.91 cm) Bin Drain 44.00" (111.76 cm) Installation Note Minimum installation 34.00" (86.30 cm) 30.00" (76.20 cm) Top/sides: 8" (20.32 cm); Back is 5" (12.7 cm)

# Space-Saving Designs





|                | i-500<br>B-400          | i-500<br>B-570   |
|----------------|-------------------------|--|
| Height         | 59.50"<br>151.13 cm     | 71.50"<br>181.61 cm  |
| Width          | 30.00"<br>76.20 cm      | 30.00"<br>76.20 cm   |
| Depth          | 34.00"<br>86.30 cm      | 34.00"<br>86.30 cm   |
| Bin<br>Storage | 290 lbs.<br>131.54 kgs. | 430 lbs.<br>195.04 kgs.  |
|                | Width Depth Bin         | B-400 Height 59.50" 151.13 cm Width 30.00" 76.20 cm Depth 34.00" 86.30 cm Bin 290 lbs. |

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

| Specifications    |                    | Ice Production 24 Hours |  | Power Usage<br>kWh/100 lbs.@90°Air/70°F | Water Usage/100 lbs.<br>45.4 kgs. of Ice |               |                 |
|-------------------|--------------------|-------------------------|--|---|--|---------------|-----------------|
|                   | Model              | Ice Shape               | 70°Air/50°F Water  | 90°Air/70°F Water                       | 1 Ph                                     | Potable Water | ENERGY<br>STAR* |
| AIR-COOLED        | IR-0500A regi      | regular                 | 500 lbs.   | 370 lbs.                                | 5.94                                     | 19.9 Gal.     | *               |
|                   |                    |                         | 227 kgs.   | 168 kgs.                                |  | 75.3 L        |                 |
|                   |                    | dice                    | 530 lbs.   | 390 lbs.                                | 5.79                                     | 19.9 Gal.     | *               |
| R-C               | ID-0502A           |                         | 240 kgs.   | 177 kgs.                                |  | 75.3 L        |                 |
| Ι                 | IY-0504A half-dice | half-dice               | 560 lbs.   | 410 lbs.                                | 5.73                                     | 19.9 Gal.     | *               |
|                   |                    |                         | 254 kgs.   | 186 kgs.                                |  | 75.3 L        |                 |
|                   | regular            | regular                 | 500 lbs.   | 420 lbs.                                | 4.58                                     | 19.9 Gal.     | NA              |
|                   | IK-0501W           | R-0501W                 | 227 kgs.   | 191 kgs.                                |  | 75.3 L        |                 |
|                   | ID-0503W dice      | dice                    | 550 lbs.   | 430 lbs.                                | 4.58                                     | 19.9 Gal.     | NA              |
| Ş                 | ID-0303VV          |                         | 249 kgs. 195 kgs. 4.58   | 4.50                                    | 75.3 L                                   | INA           |                 |
| WATER-COOLED      | IY-0505W           | half-dice               | 550 lbs.   | 440 lbs.                                | 4.52                                     | 19.9 Gal.     | NA              |
|                   | 11-0303W           | 249 kgs.                | 200 kgs.   | 4.52                                    | 75.3 L                                   | INA           |                 |
|                   | * Water-cooled Co  | ondenser Water Usag     | ge / 100 lbs. /45.4 kgs. of Ice: 165 gal/625 L. * Water-cooled models are excluded from ENERGY STAR qualification. |   |  |               |                 |
| REMOTE-<br>COOLED | ID-0592N dice      | 480 lbs.                | 430 lbs.   | 5.79                                    | 19.9 Gal.                                |               |                 |
|                   |                    |                         | 218 kgs.   | 195 kgs.                                | 5./9                                     | 75.3 L        | *               |
|                   | IY-0594N half-dice | 510 lbs.                | 440 lbs.   | 5.73                                    | 19.9 Gal.                                |               |                 |
|                   |                    |                         | 231 kgs.   | 200 kgs.                                | 5.75                                     | 75.3 L        | *               |

Order ice storage bin separately. Ice storage bin and JC-0495 remote condenser must be ordered separately. Consult remote condenser specification sheet for details.

#### Accessories

# LuminIce™ Growth Inhibitor reduces yeast and bacteria growth for a cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



Arctic Pure®
Water Filters
Reduces

Reduces sediment and chlorine odors for better tasting ice.



AuCS® schedules and performs routine ice machine cleaning

automatically.



4769C ©2014 Manitowoc 2/14 Continuing product improvement may necessitate change of specifications without notice.

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

