

Heater Proofer - Insulated with New Digital Drawer 35% Energy Savings! 100% Pre-Tested Electrical Assembly

- Heavy Duty, aluminum construction designed for durability.
- Forced air design provides even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Front casters are provided with brakes.
- "Proof/humidity" mode: Up to 95% RH at 110°F (43°C)
- "Heat" mode: Maximum Temperatures up to 180°F (82°C)
- Corner bumpers provide protection to unit, associates & fixtures.
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on the inside door frame.
- Door opens 270 degrees. Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- Drip Trough catches condensation. Internal water pan collects condensation or is used in proofer mode.
- Pan Capacity: 35 - 18" x 26" pans

Features of the new digital drawer:

- Circuit breaker to provide over current protection to the entire heater proofer.
- LED lights to show necessary temperatures for heating & proofing have been reached.
- Digital thermometer provides more accurate calibrations
- Easy to use digital control.
- Separate read out displays clearly shows settings for humidity and temperature.
- lights to indicate low water level and low temperature

Electrical specifications:

- 120 Volt-60 Hz, NEMA 5-15P
- 1500 Watts: 15.0 AMPS - Plug into any standard 110 outlet.



Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
INHPL-1836C-DGT	1079013	21 ^{1/2}	546	32	813	66 ^{3/4}	1695	154	106

Caster Information

Swivel Plate Caster with 5" Polyurethane Wheel 738A (128784)
Swivel Plate Caster with 5" Polyurethane Wheel & Brake 738ABK (204185)
5" Polyurethane Wheel 7112 (122180)
Freight Class: 100