

KMS-830MLH

SERENITY SERIES

CUBER ICE MACHINE

Item # _____

Project: _____

Qty: _____

*AutoCad available on KCL

KMS-830MLH

I/13

Item # 13281

CUBER DIMENSIONS

W x D x H

KMS-830MLH
30 x 16 1/2 x 29

CONDENSING UNIT DIMENSIONS

W x D x H




Installation Dimension*
SRK-8H / SRK-8H3
35 11/16 x 25 3/8 x 37
*Dimensions include legs

Actual Dimension
SRK-8H / SRK-8H3
33 5/8 x 22 1/2 x 22

KMS-830MLH

Remote Air-Cooled
Shown on an optional
Lancer 30" Dispenser



- Up to 820 lbs. of ice production per 24 hours
- Ice on beverage design
- Less heat in the kitchen
- Minimized noise
- Durable stainless steel exterior
- Individual crescent cube
- Protected by H-GUARD Plus Antimicrobial Agent 
- CycleSaver® Design 
- EverCheck® alert system 
- Stainless steel evaporator
- CFC / HFC Free foam
- R-404A Refrigerant
- Not recommended for side-by-side application



ISO 9001:2015 Q14001

Warranty

Valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in other countries.

Three Year - Parts & Labor on entire machine.

Five Year - Parts & Labor on: Evaporator.

Five Year - Parts on: Compressor, air-cooled condenser coil.



© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA 30269

TEL 1-800-438-6087

FAX 1-800-345-1325

www.hoshizaki.com

A City Discount

KMS-830MLH SERENITY SERIES

DIMENSIONS
W x D x H
KMS-830MLH
30 x 16 1/2 x 29

Installation Dimension*
SRK-8H / SRK-8H3
35 11/16 x 25 3/8 x 37
*Dimensions include legs

Actual Dimension
SRK-8H / SRK-8H3
33 5/8 x 22 1/2 x 22

REMOTE AIR-COOLED / SRK-8H

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	820	785	737
80°	793	739	691
90°	785	700	652

REMOTE AIR-COOLED / SRK-8H3

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	791	761	711
80°	768	722	667
90°	761	690	635


UTILITY CONSUMPTION

Model Number	Ice Production Per Cycle	KWH per 100 LBS.	Potable Water Gal. per 100 lbs.	Condenser Water Gal. per 100 lbs.
	Lbs.	Cubes	90/70	90/70
KMS-830MLH with SRK-8H	13.6	680	5.50	16.0
KMS-830MLH with SRK-8H3	12.5	680	5.40	16.0

SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
KMS-830MLH with SRK-8H	Remote Air-Cooled	9.1	20	137 lbs. 206 lbs.
KMS-830MLH with SRK-8H3	Remote Air-Cooled	7.5	20	137 lbs. 206 lbs.

KM CUBE DIMENSIONS



ELECTRICAL & PLUMBING / KMS-830MLH

- 115V/60/1 - Voltage supply for the KMS Ice Maker is supplied from the SRK Remote Condenser
- 1/2" FPT copper or equivalent independent potable water supply
- 3/4" FPT independent drain connection

CONDENSER UNIT / SRK-8H

- 208-230/60/1 (3 wire with neutral for 115V)
- 20 amp Max Fuse/HACR Breaker Size


CONDENSER UNIT / SRK-8H3

- 208-230/60/3
- 20 amp Max Fuse/HACR Breaker Size




© HOSHIZAKI AMERICA, INC.


618 Hwy. 74 S., Peachtree City, GA 30269




FRONT VIEW



SIDE VIEW




BACK VIEW



BOTTOM VIEW

SRK-8H / SRK-8H3 Remote Condensing Unit (Sold Separately)
For Use with KMS-830MLH




FRONT VIEW



Tubing Kits - REQUIRES FIELD BRAZING
(Sold Separately)

- 25' HS-0250
- 35' HS-0251
- 55' HS-0252

Voltage supply for the KMS Ice Maker is supplied from the SRK Remote Condenser.



TOP VIEW

OPERATING LIMITS

- Ambient Temp Range 45 - 100°F
- Water Temp Range 45 - 90°F
- Water Pressure 10 - 113psig
- Voltage Range 187 - 253V

CONDENSING UNIT

- Voltage Range 187 - 253V
- Ambient Temp Range -20 - 122°F

SERVICE

- Panels easily removed and all components accessible for service.

TEL 1-800-428-6087

FAX 1-800-345-1325

www.hoshizaki.com

Printed in U.S.A.

A City Discount

