

**Refrigeration Equipment
Reach-In Freezer, 1 Door, 25
cu.ft - Stainless Steel (R290)**

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738279 (KCHRI25R1DFE)

1-door reach-in freezer,
stainless steel, 25 cubic feet,
R290 refrigerant gas, -8/+5°F
- Energy star

Short Form Specification

Item No. _____

1 full door freezer with door and bottom panel in 430 stainless steel, exterior back, side and top panels in prepainted steel; interior back, side, top and bottom panels in white High Impact Polystyrene.
Control with cabinet temperature display. Self-closing and on-site reversible door feature with lock and key. Temperature range: - 8 °F min / 5 °F max.

R290 gas in the refrigeration circuit.
ETL Safety and Sanitation certifications.
3/5 Years warranty.

Main Features


- External temperature display.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmental impact.
- Back bottom mounted cooling unit guarantee an easy access and cleaning.

Construction


- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.
- PVC shelves.

APPROVAL: _____

Front




Side



EI = Electrical connection

Top



Electric

Supply voltage:

738279 (KCHRI25R1DFE) 115 V/1 ph/60 Hz

Current consumption:

2.3 Amps

Plug type:

USA NEMA 5-15P

Key Information:

Door hinges:	Right Side
Capacity (Cu. Ft.)	25
External dimensions, Width:	30 9/16" (776.99 mm)
External dimensions, Depth:	28 3/4" (730 mm)
External dimensions, Height:	77 9/16" (1970 mm)
Number and type of doors:	1 ; Full
Number and type of grids (included):	3 - Vinyl-Coated steel
Type of external material:	Prepainted Steel
Type of internal material:	White Polystyrene
External Door material:	430 AISI
Warranty:	3 / 5 years
External door material:	Stainless Steel

Refrigeration Data

Compressor Horsepower:	1/6
Refrigerant type:	;R290
Operating temperature min.:	-7.6 °F
Operating temperature max.:	5 °F
Condenser type:	Fin & tube
Defrost type:	auto defrost