



Model: _____ Item #: _____ Date: _____
Project: _____ Qty: _____ Approved By: _____

Royal Series Two Compartment Bar Sinks

Royal Series Underbar



KR19-22C

Specifications

Sink Bowl	■ 20 gauge stainless steel 10" x 14" x 10" deep
	■ Furnished with 1-1/2" IPS rear corner drain and 7-1/2" overflow pipe
Drainboard	■ 20 gauge stainless steel reinforced with welded braces every 6"
Front Apron	■ 20 gauge stainless steel clad over 20 gauge galvanized steel
Sides	■ 20 gauge stainless steel
Backsplash	■ 20 gauge stainless steel
Back & Bottom	■ 20 gauge galvanized steel
Legs	■ 1-5/8" tubular 16 gauge stainless steel with grey plastic bullet foot
Plumbing	■ Hot/Cold Water: 1/2" IPS
	■ Drain: 1-1/2" IPS
Faucet	■ 4" OC wall or deck mount faucet and ceramic cartridge valves




Standard Features

- Royal Series wall mount faucet & drains w/ overflows included
- KR19 includes a wall mount faucet
- KR24 includes deck mount faucet
- 1-1/2" left rear corner drains (Model 23-122)




WARNING: Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes.



Model	Depth (Front to Back)	Length (A)	Drainboard Size		Left Side to Drain (C)	Bowls	Bowl Location	Wgt. (lbs.)
			(B)	(B)				
KR19-22C	19"	24"	-	4"	4"	2	Center	50
KR19-32L	19"	36"	12"	4"	4"	2	Left	53
KR19-32R	19"	36"	12"	15"	15"	2	Right	53
KR19-42L	19"	48"	24"	4"	4"	2	Left	55
KR19-42R	19"	48"	24"	21"	21"	2	Right	55
KR19-42C	19"	48"	(2) 12"	27"	27"	2	Center	55



Model	Depth (Front to Back)	Length (A)	Drainboard Size		Left Side to Drain (C)	Bowls	Bowl Location	Wgt. (lbs.)
			(B)	(B)				
KR24-22C	24"	24"	-	4"	4"	2	Center	55
KR24-32L	24"	36"	12"	4"	4"	2	Left	58
KR24-32R	24"	36"	12"	15"	15"	2	Right	58
KR24-42L	24"	48"	24"	4"	4"	2	Left	60
KR24-42R	24"	48"	24"	27"	27"	2	Right	60
KR24-42C	24"	48"	(2) 12"	15"	15"	2	Center	60



NOTE: Letter at end of Model Number represents Bowl Location