

Royal Two Compartment Bar Sinks

Model:		- NOE
Item #:	Quantity:	NSt
Project:		



· Sink Bowl:

20 gauge 304 series stainless steel 10" x 14" x 10" deep. Furnished with 1" IPS rear corner drain and 7 1/2" overflow pipe.

Drainboard:

20 gauge 304 series stainless steel reinforced with welded braces every six inches.

Front Apron:

20 gauge 304 series stainless steel clad over 20 gauge galvaneal.

Sides:

20 gauge 304 series stainless steel.

Backsplash:

20 gauge 304 series stainless steel.

Back and Bottom:

20 gauge galvaneal.

Legs:

1 5/8" tubular 16 gauge stainless steel with grey thermoplastic bullet foot.

Faucet (included):

Royal Series 4" center wall or deck mount faucet with cartridge valves. (1800 Series-wall mount, 2100 Series-deck mount)

Plumbing:

1/2" IPS hot and cold water
1" IPS drain connection

Accessories

- ☐ Built-in 20 gauge Sound Deadened Krowne Royal Single Speedrail
- ☐ Built-in 20 gauge Sound Deadened Krowne Royal Double Speedrail
- □ Towel Ring
- ☐ Waste Manifold
- ☐ Perforated Basket
- ☐ Side Splash (specify left or right)
- ☐ Corner Return (specify left or right)
- ☐ 6" longer Stainless Steel Legs

Approved By:	
- ·	






Royal Two Compartment Bar Sinks


NSF

Model: _____ Item #: _____ Quantity: ____ Project: _____

1800 Series




(A)	
10" 10" -	36.5*





Model	Length (A)	Drainboard	Left Side	Bowl(s)	Weight
Numbers		B	to Drain	Location	Ibs
KR18-22C KR18-32L KR18-32R KR18-42L KR18-42R KR18-42C	2'-0" 3'-0" 3'-0" 4'-0" 4'-0"	n/a 12" 12" 24" 24" 12" (2 ea.)	4" 4" 15" 4" 27" 15"	Center Left Right Left Right Center	60 80 80 105 105 105

Note: Letter at end of Model # repesents Bowl location.

2100 Series







Model Numbers	Length (A)	Drainboard B	Left Side to Drain	Bowl(s) Location	Weight Ibs
KR21-22C KR21-32L KR21-32R KR21-42L KR21-42R KR21-42C	2'-0" 3'-0" 3'-0" 4'-0" 4'-0"	n/a 12" 12" 24" 24" 12" (2 ea.)	4" 4" 15" 4" 27" 15"	Center Left Right Left Right Center	60 80 80 105 105 105

Note: Letter at end of Model # repesents Bowl location.

Mechanical Requirements:

1/2" IPS Hot and Cold Connection.

1" IPS Drain Connection.

Approved By:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Krowne Metal Corporation

257 Verona Ave. Newark, New Jersey 07104

www.krowne.com

sales@krowne.com

Phone: 800-631-0442 FAX: 973-485-1424