

Heater Proofers - Non-Insulated Universal Runner 100% Pre-Tested Electrical Assembly



- Non-insulated - Heavy duty aluminum construction.
- Air baffle and circulating air blower provide even heat distribution.
- Proofing/Heating module with dual elements is 120VAC, 14 AMP, cycle, 1220 watts. Plugs into any standard 110 outlet.
- Removable chrome pan slides for variable spacing and for easy cleaning.
- Clear door for easy viewing of product while retaining heating because doors are opened less. Door gasket prevents heat loss due to complete seal around the door. Field reversible door for right or left hanging standard. Magnetic door latch for keeping door closed during transport. Easy pull handle for opening.
- Easy to read LED thermometer.
- 25 pan slides hold a variety of pan configurations from sheet pans to steam table pans.
- Easy dual proof/heat control:
 - “Proof” mode: Humidity from 30% to 95%.
Temperatures up to 115°F (46°C)
 - “Heat” mode: Nominal Temperatures up to 185°F (85°C)
- Corner bumpers provide protection to unit, associates and fixtures.
- 5" polyurethane plate casters standard with brakes for easy maneuverability.

Equipment Guide

- ✓ **BEST**
- ✓ **HEAVY DUTY USE**
- ✓ **1YR WARRANTY**
- ✓ **HACCP HELPER**
- ✓ **NSF** **UL**
- ✓ **NEW**
- ✓ **EXPRESS SHIP**



NHP-PD-UN
Removable Drawer
Makes Cleaning Quick & Easy

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



Magnetic Door Latch



Field Reversible Door Mount



Adjustable Runners

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1825-UN	640067	24	610	32	813	70	1,778	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

For replacement parts please see page 125.

Freight Class: 100

