NOR-LAKE, INCORPORATED 727 Second Street P.O. Box 248 Hudson, Wisconsin 54016

715-386-2323 866-961-5253 Parts 800-388-5253 Service 715-386-4291 FAX www.norlake.com

800-955-5253

## ADVANTEDGETM GLASS DOOR BACK BAR REFRIGERATORS



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

#### SPECIFICATIONS FOR: NLBB59G, NLBB69G, NLBB79G, NLBB95G

Finish: Heavy duty stainless steel top and black vinyl coated steel exterior front, sides and back.

Galvanized steel interior walls and stainless steel floor.

Insulation: Foamed-in-place 1-1/2" CFC-Free polyurethane insulation.

Hardware: Glass doors with locks, magnetic door gaskets, plastic breaker strips around door openings

to limit the formation of any condensation. Two adjustable epoxy coated shelves per door

section standard. Interior fluorescent light.

Electrical: 115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P Plug.

Refrigeration: Self-contained forced air R-134a capillary tube refrigeration system. Temperature range from

+35°F to +38°F. Adjustable temperature control.

Approvals: ETL Safety and Sanitation listed

#### STANDARD FEATURES

- Adjustable temperature control
- Black vinyl steel coated front, sides and back exterior
- Fluorescent interior light
- Free flowing air system at all times to ensure uniformly cooled products
- Heavy duty 18 gauge stainless steel top
- Slide out condensing unit
- Temperature range: +35°F to +38°F
- ETL Safety and Sanitation listed
- Approved to NSF standard for bottled or canned products
- Warranties: 3 year parts & labor, 5 year compressor


### **OPTIONAL FEATURES\***


- Epoxy coated flat shelves with clips
- Floor rack
- Shelves with product guides
- 3" casters





Nor-Lake, Inc. Registered to ISO 9001:2008 File No. 10001816












FRONT NLBB69G


FRONT NLBB59G

**TOP** NLBB59G


**SIDE** 



#### **TOP** NLBB69G




# **FRONT** NLBB79G




## SPECIFICATIONS

Models	NLBB59G	NLBB69G	NLBB79G	NLBB95G
Crated Height	43"	43"	43"	43"
Crated Width	60-1/2"	70-1/2"	81"	96-1/2"
Crated Depth	30"	30"	30"	30"
Crated Weight (lbs.)	312	360	378	440
Interior Height	31-3/4"	31-3/4"	31-3/4"	31-3/4"
Interior Width	44-9/16"	54-9/16"	65-1/16"	80-9/16"
Interior Depth	24-3/4"	24-3/4"	24-3/4"	24-3/4"
Overall Height	37-1/4"	37-1/4"	37-1/4"	37-1/4"
Overall Width	59-1/2"	69-1/2"	80"	95-1/2"
Overall Depth	28-3/16"	28-3/16"	28-3/16"	28-3/16"
Gross Cubage (ft.3)	23.7 (670)	28 (793)	30.8 (872)	39.2 (1112)
Number of Shelves	4	4	6	6
Condensing Unit Size	1/3	1/3	1/3	1/3
Refrigerant	R-134a	R-134a	R-134a	R-134a
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes
Nema Plug Configuration	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	6.6	6.6	6.6	7.2
12 oz. Can Capacity	640	800	920	1160
12 oz. Bottle Capacity	432	540	621	810

Specifications subject to change without notice.



FRONT NLBB95G



NLBB95G







Revision Date: 03/13 © 2013 NOR-LAKE, INC. Printed in the U.S.A. Part Number: 143583