

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

## **Undercounter Refrigerator - Drawers**

Undercounters PRO Series

Model: PUR-60-D4-N

#### **Patented Self-Cleaning Condenser**



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



#### \_\_\_ FEATURES & BENEFITS =\_\_

#### ■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

Lifetime guaranteed heavy duty handles

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ Magnetic drawer gaskets

Magnetic drawer gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

- Refrigerator holds 33°F ~ 38°F for the best in food preservation
- Built to maintain NSF standard temperatures in 100°F ambient
- Each top drawer accommodates up to 6" deep, one (1) full size pan with three (3) 1/6 size pan or three (3) 1/3 size pans with three (3) 1/6 size pan or nine (9) 1/6 size pans. And each bottom drawer accommodates up to 6" deep, one (1) full size pan or two (2) 1/3 size pans with two (2) 1/6 size pans or six (6) 1/6 size pans (drawer pans not included)











							interter interte	K C. C. T.
Model	Swing Doors	Drawers	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H <sup>†</sup> (inches)
PUR-60-D4-N	-	4	17	-	1/6	8.9	298	601/4 x 30 x 30

### Model: PUR-60-D4-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	8.9				
Compressor HP	1/6				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	17				
Ext. Length Overall (in.)	601/4 (1530mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.)†	30 (762mm) -				
# of Doors					
# of Drawers	4				
# of Shelves	-				
Net Weight (lbs.)	268				
Gross Weight (lbs.)	298				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

# 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor


### STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- · Standard 4" dia. swivel casters with locks on the front set
- \*\* Lead time applies. Please contact your sales representative for more details to order.


#### OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Stainless steel double overshelf: TSOS-5R
- Back splash guard: TU-60B

#### **PLAN VIEW** (unit: inch)



**TOP VIEW** 



Ver.20200526













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Depth does not include 2" for drawer handles & rear spacers.

<sup>†</sup> Height does not include 5-3/8" for caster height.