



QUICK SHIP

Walk-In Coolers & Freezers With Matching Refrigeration Systems

Features

- Available from 4' x 6' to 10' x 14'
- Available in 3 heights: 6'7" & 7'7" with floor, 7'4" less floor
- Automatic condensate vaporizer. No drain line required on indoor units (QS Series models with Capsule Pak systems)
- Cooler or freezer models
- Door closer spring actuated
- Exterior finish is corrosion resistant stucco embossed coated steel
- Full 4" panel foamed-in-place with EPA-compliant polyurethane insulation
- Indoor or outdoor models
- · Installation is fast and easy
- Deadbolt locking handle for security

- Adjustable spring loaded door hinge
- High output low profile LED light positioned above the door to prevent interference with shelving or product
- Temperatures: +35°F and -10°F
- 15 year panel warranty
- Approvals:
 - NSF, UL flame spread 25 or less on foam cores
 - UL and CSA electrical listing on door sections
 - City of Houston listed
 - California State listed
 - CN UL flame spread listed
 - DOE compliant
 - Oregon State listed
 - USDA accepted

Options

- · Heights: 8'7" with floor, 8'4" without floor
- · Floor tread plate kit
- · Exterior ramp
- Door & frame kickplates (shipped loose)
- Vinyl strip curtains for entry doors (shipped loose)
- · Condensing unit air deflector kit
- Door hood (outdoor models)
- Heater kit for outdoor use where ambient condtions may go below 32°F
- Leak detector/alarm (may be a requirement in some areas)
- Electric vaporizer
- · Five year compressor warranty
- Specially designed shelving kits
 - Flexible shelf adjustment in 1" increments
 - Shelving layouts utilize maximum spacefor storage leaving the door opening clear of end standards
 - Green Kote[™] special epoxy-coated finish provides extra protection from acidic foods
 - Quick and easy assembly
 - Rigid construction
 - Stronger shelves
 - Optional U-shaped systems



Shelving kits





Door & frame kickplates Exterior floor ramps (shipped loose)

M-Series Remote Refrigeration Systems

When the application calls for a remote refrigeration system, Master-Bilt provides an M-Series condensing unit and E-Series evaporator coil sized to fit requirements.

- Designed to withstand the harshest conditions,
 M-Series condensing units contain the most efficient combination of condenser coil, fan and fan motor available
- All components are pre-wired and factory assembled on a galvanized steel angle leg base
- Horsepower ranges from ¹/₂ to 6 H.P.
- M-Series units are provided with factory pre-mounted and wired time clocks in both medium and low temp versions
- E-series evaporator coils are ready to mount in position and are available in air (off cycle) defrost for coolers and electric defrost for freezers
- Each coil is also furnished with a properly-sized expansion valve and room thermostat
- Electric defrost coils feature defrost termination-fan delay controls and drain line heaters.
- Standard energy efficient EC motors on quick ship coils.

- One year limited parts and labor warranty and an extended four year warranty on the compressor
- Dedicated medium temp outdoor condensing units meet the DOE requirement of a minimum AWEF rating of 7.61 (Btu/W-h).



M-Series condensing units are standard with generously-sized condensers for maximum performance in harsh environments. Each unit is pre-piped and pre-wired at the factory for convenient installation.

Energy efficient EC motors are standard on Quick Ship evaporator coils.



Capsule Pak™ Refrigeration Systems


Specified for QS Series models 14' long and under as well as combination models.

Designed for quick and simple installation, Capsule Pak systems consist of a pre-charged quick-connect condensing unit and evaporator coil.

- Easy installation with no floor drain required on indoor models
- Easier servicing with many evaporator components accessible from inside/underneath vs. on top
- Substantially larger evaporator coil improves performance and energy efficiency
- Standard Copeland Scroll[™] compressors on most models for increased efficiency
- Electronic controller standard on demand defrost models for increased reliability, connectivity and food safety
- Eco-friendly R449A refrigerant provides a 64% reduction in GWP vs. previous R-404A refrigerant
- DOE*, SNAP and CARB compliant
- Industry leading 18 month parts and labor and five year compressor warranty



The Capsule Pak evaporator grille mounts flush in a standard 4" thick ceiling panel allowing maximum storage space inside the walk-in.



Capsule Pak units are available in both indoor and outdoor ceiling mount models. Outdoor models are standard with a crankcase heater and head master.

^{*}Dedicated medium temp outdoor condensing units meet the DOE requirement of a minimum AWEF rating of 7.61 (Btu/W-h)



For the latest product information and specifications go to www.master-bilt.com/products/products.htm.











