

## SUBMERSIBLE SCALE, 22 LB

The newest member of the *Submersible Scales* series, the Submersible Scale, 22 lb (SD2220) was designed for demanding foodservice kitchens. It is NSF<sup>®</sup> Certified, sturdy and programmable, featuring low/high limit alerts with the color-coded backlit display. The heavy-duty stainless steel SD2220 is submersible with an impressive IP68 rating, which certifies it to be protected from water up to 4.9 feet/ 1.5 meter for 60 minutes and completely protected against dust. Also available in an 11 pound capacity.



### FEATURES

- NSF<sup>®</sup> Certified
- Low/high limit alerts with backlit display
- Submersible (IP68: protected from water up to 4.9 feet/1.5 meter for 60 minutes, completely protected against dust)
- Hold mode
- Programmable
- Tare function
- Field calibration
- Stainless steel housing
- Removable stainless steel platform
- Rechargeable battery & power adapter

### SPECIFICATIONS

<b>Measurement Range:</b>	22 lb/10 kg/352 oz by oz, / oz, kg, g, lb:oz, lb:/ oz, lb
<b>Display Size:</b>	3.35 W x 1.3 H (in)/8.5 W x 3.3 H (cm)
<b>Platform Size:</b>	6.4 W x 7 L (in)/16.2 W x 18.2 L (cm)
<b>Product Dimensions:</b>	8.0 W x 2.0 H x 10.0 D (in)/ 20.3 W x 5.0H x 25.1 D (cm)
<b>Resolution:</b>	0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb
<b>Power:</b>	AC Adapter: 100-240 VAC 50/60Hz input, 9V DC (1000mAh) output included; Battery: built-in rechargeable 4.8V 1800 mAh included
<b>Weight:</b>	46.31 oz / 1313 g (including battery)
<b>UPC:</b>	0 18436 00846 0
<b>Other:</b>	<ul style="list-style-type: none"> <li>• Selectable units</li> <li>• Stability indication</li> <li>• Overload indication</li> <li>• Low battery and charging indication</li> <li>• On/off button</li> <li>• Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used</li> </ul>

### AVAILABLE

11-23

