

Project	Item Number	Quantity
---------	-------------	----------

--	--	--

**SFG500 SERIES**



## SFG500 SERIES

# REVERSIBLE DOUGH SHEETER

**Models:**

- SFG 500 T Floor Model
- SFG 500 TM Floor Model



**REVERSIBLE DOUGH SHEETER**

**Features**

- Reversible dough sheeter.
- Hand and foot pedal operation.
- 0 to 1.9" (48mm) adjustable cylinder separation changes dough thickness.
- Hard chrome polished cylinders.
- Tables fold upright for storage and movement.
- Powerful 3/4 HP motor.
- Sheets dough onto rolling pins to allow for transport of rolled dough to work area.
- Interlock switches protect operator from injury if safety guard is opened.
- Pivoting and removable arms.
- Convenient storage in base for rolling pins.
- Cord and plug.

**Standard Accessories**

- Heavy duty hardwood rolling pins.
- Designated area for flour while operating machine.

**Warranty**

- One-year, on-site parts & labor warranty

**Univex Corporation**

**WARRANTY DETAILS**

The SFG500 Sheeters carry a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8:00 a.m. and 5:00 p.m. Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.




Univex Corporation  
www. Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 USA  
Telephone (800) 258-6358 Fax: (800) 356-5614  
Int'l Tel. (603) 893-6191 Int'l Fax: (603) 893-1249

# REVERSIBLE DOUGH SHEETER

# SFG500



**Shipping Information:**  
Freight Class: 85

	SFG500 T	SFG500 TM
Net Weight:	375lb.(170Kg)	408lb.(185Kg)
Shipping Weight:	485lb. (220Kg)	518lb. (235Kg)

Shipping Crate Dimensions:

Height:	61.4" (1560mm)	72.8" (1560mm)
Width:	56.0" (1420mm)	56.0" (1420mm)
Depth:	36.6" (930mm)	36.6" (930mm)
Cubic measure:	73ft <sup>3</sup> (2.06M <sup>3</sup> )	73ft <sup>3</sup> (2.06M <sup>3</sup> )

**Dimensions:**

	SFG500 T	SFG500 TM
A) Overall length:	80.1" (2035mm)	117.7" (2990mm)
B) Base length:	29.5" (750mm)	29.5" (750mm)
C) Machine width:	37.6" (955mm)	37.6" (955mm)
D) Overall height:	50.0" (1270mm)	50.0" (1270mm)
E) Belt width:	19.7" (500mm)	19.7" (500mm)
F) Length folded:	29.5" (750mm)	43.3" (1100mm)
G) Height folded:	58.3" (1482mm)	75.6" (1920mm)
H) Table length (2 X)	27.6" (700mm)	46.5" (1180mm)

**Motor:** 3/4 hp. Capacitor start

**Drive:** Chain drive.

**Electrical:**  
220V,60HZ,3PH,1.8A

Contact factory for additional voltages and certifications

**Controls:** Stop and start push buttons. Manually adjustable space between rolling cylinders adjusts in increments from 0" to 1.9" (0 to 48mm). Hand and foot pedals for shifting conveyor direction.