

Blendtec® Stealth™

Commercial Blender



Key Features

- Quietest commercial blender in the world...ever
- Powerful 15Amp, 1800 Watt direct-drive motor
- Easy-to-use illuminated capacitive touch interface
- Slider control provides ultimate manual speed control
- 36 pre-programmed blend cycles
- 6 completely customizable blend cycle buttons
- USB programming port and online design tools allow for easy updating and complete cycle customization
- Easy-to-remove, easy-to-clean enclosure. No fasteners
- One of the smallest footprints in its class
- Compatible with all Blendtec jars and accessories
- In-counter installation option available

Specifications

Model		CQB1 / IQB1 (STEALTH)	
Configuration	In or On counter		
Control System	Capacitive Touch		
Programmable Buttons	6		
Pre-programmed Cycles	36		
Cycle Counter	Yes		
Display	LCD Type		
Electrical Characteristics			
Power Consumption	1800W		
Power Output	Varies with speed		
Power Source	120V, 50-60HZ, 15A, Single Phase		
Plug Configuration	Nema 5-15P		
Frequency	50-60Hz		
Power Cord Length	7' (2.1m)		
Package Configuration		QTY Included	
CQB1 / IQB1 Motor Base		1	
Stealth Sound Enclosure		1	
Blender Jars (FourSide or WildSide)		2	
Blender Jar Lids (Hard or Soft)		2	
Assembled Footprint		Counter Mounting	
		In-Counter	On-Counter
Height		12.72" (32.31 cm)	17.22" (43.74 cm)
Width		8.59" (21.82cm)	8.55" (21.71 cm)
Depth		9.11 (23.14 cm)	9.06" (23.01 cm)
Under Motor Cabinet Clearance			6 1/2" (16.51 cm)
Warranty Information			
Motor Base		3 Year / 20,000 cycles	
Drive Socket		Lifetime	
Blender Jar, FourSide		1 Year	
Blender Jar, WildSide		1 Year	
Blender Jar Lid		None	
Weight/Shipping Information			
Net Weight		14.55 lbs (6.60 kg)	
Shipping Weight		21.7 lbs (9.8 kg)	
Shipping Carton Dimensions		29 1/2" L x 14 1/2" W x 13 1/2" H (749.3mm x 368.3mm x 342.9mm)	
Certification Information			
Electrical/Safety		ETL (UL and CSA equivalent) ***Pending	
Sanitation/Food Safety		NSF (Standard 8)	