- **GMBS452D**   51"L x 42-3/4"D x 51-5/8"H
- **GMBS552D**   62-3/4"L x 42-3/4"D x 51-5/8"H
- **GMBS652D**   75-3/8"L x 42-3/4"D x 51-5/8"H

GMBS652D

Included
- LED top & shelf lights
- Lift-up front glass
- Non-refrigerated for ambient display
- One year parts & labor warranty
- Stainless steel rear exterior

| Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Laminate (stock colors)	• Laminate (non-stock colors) • Powder coated (stock/non-stock colors) • Powder coated Silversan Black • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• Stainless steel
LOWER FRONT PANEL COLOR	• Powder coated Silversan Black	• Powder coated (stock/non-stock colors) • Stainless steel
BASE SUPPORT	• Rail system for shims	
BUMPER FRONT	• 1" Boston bumper (specify color)	• 1" Stainless steel plate rail bumper
END PANELS	• Full w/stainless steel mirror interior	• Cutaway w/glass • None (specify per line-up)
FRONT GLASS	• Curved	• Flat angled
PRICE TAG MOLDING	• None	• 1" Price tag molding (black or silver) • Universal price tag molding (clear w/ open top)
REAR DOORS	• Clear glass rear sliding doors	• Reflective glass rear sliding doors
SHELVING	• 16" & 16" Solid shelving	• 16" & 16" Glass shelving
LIGHTS	• LED 3500K w/ frosted lens	• LED 4000K w/ frosted lens
ELECTRICAL CONNECTION	• Electrical leads	
MISCELLANEOUS		• Front glass lock • Rear door lock

Intended Environment:	Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.	
Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Unpackaged non-refrigerated products	Ambient

PLAN VIEW

GMBS452D = 24 3/8"
GMBS556D = 30 1/4"
GMBS652D = 36 1/2"

TOE KICK
TOE KICK

1 1/8" TYP
GMBS452D, GMBS552D, GMBS652D CASE FRONT

SIDE VIEW

CURVED FRONT GLASS
w/ GLASS SHELVES SHOWN

STRAIGHT FRONT GLASS
w/ SOLID SHELVES SHOWN

NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH ¾" OR 1½" PVC TUBE).
- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.
- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications															
Model	L"	L1"	L2"	System Circuit Volts		Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
GMBS452D	48.75	51.00	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.70	33	2+G	Leads Single	N/A	N/A	N/A	800
GMBS552D	60.50	62.75	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.99	120	2+G	5-15P or L5-15P	N/A	N/A	N/A	1,100
GMBS652D	73.13	75.38	.00	Ambient/Lights (N/A)	Circuit #1	110-120	1	60	0.70	50	2+G	5-20P	N/A	N/A	N/A	1,320

*** Does not include electric defrost on freezer models.

Regulatory Approvals:	
All Models	ETL Listed to UL 65 ETL Sanitation to NSF/ANSI 2

ETL (c ETL us) INTERTEK LISTED / INTERTEK SANITATION LISTED

DOE 2017 Energy Efficiency Compliant

Important Notes:

1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle.

2) 45" minimum door entry clearance required (without shipping skid).

3) Units must be shimmed during installation to ensure the unit is level and plumb.

⚠ **WARNING:** This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.