

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Proi	iant	
110	ICCI	•

Model # : Item # :

Qty :

Model : TBP36-46FN-W(B)

Refrigerated

Bakery Cases

Available W/H :

Approval :

Bakery Display Cases

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Liboutr	



TBP36-46FN-W

TBP36-46FN-B

____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Sliding rear doors and front glass opening
 Sliding rear doors make it easily accessible and convenient to arrange products. These doors are built to withstand constant sliding open and close. The front glass opens just enough to clean the interior effortlessly.
- Digital temperature controller
- Double pane glass is tempered for safety (Front heated glass)
- Adjustable, tempered glass shelves with stainless steel front and back edges
- Stainless steel floor and airflow grille
- Rear access to compressor compartment for quick and easy service

					NATURAL Refrigerant	
Model	CU./FT.	# of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D \ge H^{\star}$ (inches)
TBP36-46FN-W(B)	9	1	1/3	6.3	504	353/8 x 271/2 x 44

* Height does not include 2-1/4" for caster height.

Bakery Display Cases

Model : TBP36-46FN-W(B)

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	6.3			
Compressor HP	1/3			
Cord Length (ft.)	81/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	9			
Ext. Length Overall (in.)	353/8 (900mm)			
Ext. Depth Overall (in.)	271/2 (700mm)			
Ext. Height Overall (in.)*	44 (1118mm)			
Shelf Size (L x D) (in.)	323/8 x 15			
# of Shelves	1			
Net Weight (lbs.)	327			
Gross weight (lbs.)	504			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Height does not include 2-1/4" for caster height.

WARRANTY : ² Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

STANDARD FEATURES

- · Self-contained system, no plumbing required
- Safety shielded LED interior lighting
- White and black color come standard
- 3" dia. swivel casters with locks on the rear set
- ** Lead time applies. Please contact your sales representative for more details to order.

(GERMAN)


KNIFE

Recommended operating conditions


TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

PLAN VIEW

(unit : inch)



FRONT VIEW



SIDE VIEW

Ver.20200518

NATURAL

Turbo Air : 800-627-0032 **GK** : 800-500-3519

Turbo air Texaking

Warranty : 800-381-7770 **AC** : 888-900-1002

