

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

**Model: TBP48-54FDN** 

# Drop-in Type Bakery Display Cases

Refrigerated Bakery Cases

## Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.





\* Bottom portion will not be visible after installation

## = FEATURES & BENEFITS =

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

# ■ Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

#### High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Digital temperature controller
- Double pane glass is tempered for safety (Front heated glass)
- Adjustable, tempered glass shelves with stainless steel front and back edges
- Stainless steel floor and airflow grille
- Sliding rear doors and front glass for product loading & unloading
- Rear access to compressor compartment for quick and easy service











Model	CU./FT.	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TBP48-54FDN	17.2	2	3/4	8.2	643	487/8 x 293/4 x 517/8

(unit: inch)

# **Model: TBP48-54FDN**

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type				
Full Load Amperes	8.2			
Compressor HP	3/4			
Cord Length (ft.)	81/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	17.2			
Ext. Length Overall (in.)	487/8 (1240mm)			
Ext. Depth Overall (in.)	293/4 (755mm)			
Ext. Height Overall (in.)*	517/8 (1318mm)			
Shelf Size (L x D) (in.)	44 <sub>1/8</sub> x 15			
	44 <sub>1/8</sub> x 13			
# of Shelves	2			
Net Weight (lbs.)	433			
Gross Weight (lbs.)	643			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

# ■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor


### STANDARD FEATURES

- · Self-contained system, no plumbing required
- · Safety shielded LED interior lighting
- 3" dia. swivel casters with locks on the rear set
- \*\* Lead time applies. Please contact your sales representative for more details to order.


#### Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

# **PLAN VIEW**



FRONT VIEW



Ver.20200514











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Height does not include 2-1/4" for caster height.